

Power Relay F

TE Internal #: 1393304-9

Maxi Relays, 12 VDC Coil Voltage, Plug-In, Monostable, DC, 90 Ω

Coil Resistance, Mounting Brackets, Power Relay F

View on TE.com >



Relays, Contactors & Switches > Relays > Automotive Relays > Automotive Plug-In Relays > Maxi Relays



Rated Coil Voltage: 12 VDC

Maxi Relay Contact Current Class: >50A

Maxi Relay Mounting Type: Plug-In

Maxi Relay Coil Magnetic System: Monostable, DC

Maxi Relay Coil Resistance: 90Ω

Features

Product Type Features

Relay Type	Power Relay F7
Electrical Characteristics	
Coil Power Rating Class	>1.5W
Current Rating (85°C)	70 A
Contact Limiting Short-Time Current	300 A
Insulation Initial Dielectric Between Contacts and Coil	500 Vrms
Insulation Initial Dielectric Between Coil/Contact Class	0 – 500 V
Coil Power Rating (DC)	1600 mW
Insulation Initial Dielectric Between Open Contacts	500 Vrms
Contact Limiting Making Current	240 A
Contact Limiting Continuous Current	70 A
Rated Voltage	12 VDC
Contact Limiting Breaking Current	70 A
Contact Switching Load (Min)	1000mA @ 5VDC
Rated Coil Voltage	12 VDC
Maxi Relay Coil Magnetic System	Monostable, DC
Maxi Relay Coil Resistance	90 Ω
Body Features	

38 g[1.3 oz]

Weight



Contact Features

Contact reatures	
Terminal Type	Plug-In, Quick Connect
Contact Arrangement	1 Form A (NO)
Contact Base Material	Silver Alloy
Maxi Relay Contact Current Class	>50A
Mechanical Attachment	
Maxi Relay Mounting Type	Plug-In
Dimensions	
Width Class (Mechanical)	25 – 30 mm
Length Class (Mechanical)	25 – 30 mm
Height Class (Mechanical)	25 – 30 mm
Width	25.9 mm[1.019 in]
Length	25.9 mm[1.019 in]
Height	24.9 mm[.98 in]
Usage Conditions	
Environmental Ambient Temperature (Max)	125 °C[257 °F]
Environmental Ambient Temperature Class	105 – 125°C
Other	

Product Compliance

Mounting Brackets

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability


With




Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Power Relay F





Customers Also Bought

















Documents

Product Drawings

V23134J1052D642-EV-CBOX

English

CAD Files

Customer View Model

ENG_CVM_1393304-9_S00F.3d_igs.zip

English

Customer View Model

ENG_CVM_1393304-9_S00F.3d_stp.zip

English

Customer View Model

ENG_CVM_1393304-9_S00F.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Automotive Relay Application Notes

English

Power Relay F7, Maxi ISO, Plug-In

English

Product Specifications

Definitions General Purpose Relays

English