



Potter & Brumfield

TE Internal #: 1423008-9

Power Relays, Standard, Monostable, DC, 1700 mW Coil Power Rating DC, 350 Ω Coil Resistance, UL Coil Insulation Class F, 24 VDC Coil Voltage

[View on TE.com >](#)

Relays, Contactors & Switches > Relays > Power Relays



Power Relay Type: **Standard**

Coil Magnetic System: **Monostable, DC**

Coil Power Rating DC: **1700 mW**

Coil Resistance: **350 Ω**

Coil Special Features: **UL Coil Insulation Class F**

Features

Product Type Features

Output Type	DC
Power Relay Type	Standard

Configuration Features

Output Switching	Random
------------------	--------

Electrical Characteristics

Insulation Initial Dielectric Between Coil & Contact Class	3500 – 4000 V
Insulation Initial Dielectric Between Open Contacts	1500 Vrms
Coil Power Rating	1.7 W
Insulation Creepage Class	8 mm
Insulation Initial Dielectric Between Adjacent Contacts	2000 Vrms
Insulation Initial Resistance	1000 MΩ
Insulation Initial Dielectric Between Contacts & Coil	4000 Vrms
Contact Limiting Making Current	30 A
Insulation Creepage Between Contact & Coil	8 mm[.315 in]



Contact Limiting Continuous Current	40 A
Output Current (Min)	.5 A
Contact Limiting Breaking Current	30 A
Coil Magnetic System	Monostable, DC
Coil Power Rating DC	1700 mW
Coil Resistance	350 Ω
Coil Special Features	UL Coil Insulation Class F
Coil Voltage Rating	24 VDC
Contact Switching Load (Min)	500mA @ 12V
Contact Switching Voltage (Max)	600 VAC
Contact Voltage Rating	277 VAC

Body Features

Insulation Special Features	6000V Initial Surge Withstand Voltage between Contacts & Coil
Product Weight	86 g[3.034 oz]

Contact Features

Contact Arrangement	2 Form A (NO)
Contact Current Rating (Max)	30 A
Contact Material	AgSnOInO
Contact Number of Poles	2
Relay Terminal Type	Panel Mount Relay

Mechanical Attachment

Relay Mounting Type	Panel Mount
---------------------	-------------

Dimensions

Length Class (Mechanical)	50 – 60 mm
Height Class (Mechanical)	25 – 30 mm
Insulation Clearance Between Contact & Coil	8 mm[.315 in]
Insulation Clearance Class	5 – 8 mm
Width Class (Mechanical)	30 – 40 mm
Product Width	34.54 mm[1.36 in]
Product Length	52.32 mm[2.06 in]
Product Height	30.73 mm[1.21 in]

Usage Conditions



Environmental Ambient Temperature (Max)	85 °C[185 °F]
Environmental Ambient Temperature Class	70 – 85 °C

Packaging Features

Packaging Method	Package
------------------	---------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 240°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Customers Also Bought



TE Part #2-34541-1
PIDG SPD 22-16 COMM 22-18MIL 6



TE Part #NB-PTCO-002
Pt100, 2.0x2.3, Class B, PTFC101B1G0



TE Part #3-647630-3
03P MTA100 HRD ASSY F/L LF



TE Part #T4030014031-000
M8.MLE.PNLREAR.3POS.STR



TE Part #796636-6
6POS 5.08MM CE VRT HDR,TRM BLK



TE Part #2-32961-1
TERMINAL,PG R 16-14 1/4



TE Part #1217151-1
187 FASTON,PIGGYBACK REC.,18-14 AWG,TPBR



TE Part #1-647557-8
CST-100 II HSG 18 POS #2 BLKD



TE Part #2-456135-6
CRIMPER, INSUL. "O" (.155")



TE Part #6-1437685-4
8TK2-48=SNAP TRACK

Documents

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_1423008-9_F.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1423008-9_F.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1423008-9_F.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[T92 Two-Pole, 30 Amp, PC Board or Panel Mount Relay](#)

English



Product Specifications

Definitions General Purpose Relays

English

Agency Approvals

[CQC_CERT_03001008772_C1](#)

English

[CQC_CERT_16002142754_C1](#)

English