7014AB - ACTIVE

Agastat

TE Internal #: 1423160-1 Time Delay Relays, Knob, 120 – 110 VAC Input, 10A@240VAC A, On-Delay, .7 – 7 seconds Delay Time, Mounting Bracket View on TE.com >



Relays, Contactors & Switches > Relays > Time Delay Relays



Type of Control: Knob Time Delay Relay Input Voltage: 120 – 110 VAC Time Delay Relay Contact Current Rating: 10A@240VAC A Mode of Operation: On-Delay Delay Time: .7 – 7 seconds

Features

Product Type Features

Product Type	Relay
Relay Type	Time Delay
Product Category	Electromechanical Relays

Magnetic Blow-Out Device	Without
Configuration Features	
Multiple Timing Ranges	Without
Electrical Characteristics	
Actuating System	AC
Time Delay Relay Input Voltage	120 – 110 VAC
Contact Features	
Contact Arrangement	4 Form C, 4PDT, 4 C/O
Type of Control	Knob
Time Delay Relay Contact Current Rating	10A@240VAC A
Delay Time	.7 – 7 seconds
Termination Features	
Termination Type	Screw Terminals
Mechanical Attachment	

C For support call+1 800 522 6752

09/18/2023 09:31PM | Page 1

7014AB

Time Delay Relays, Knob, 120 – 110 VAC Input, 10A@240VAC A, On-Delay, .7 – 7 seconds Delay Time, Mounting Bracket



Time Delay Relay Mounting Type	Mounting Bracket	
Dimensions		
Dimensions (L x W x H) (Approximate)	114.8 x 65.3 x 71.9 mm[4.523 x 2.572 x 2.832 in]	
Usage Conditions		
Operating Temperature Range	-30 – 75 °C	
Operation/Application		
Mode of Operation	On-Delay	
Other		
Repeatability (Max)	±10%	
Product Compliance For compliance documentation, visit the product page on TE.com>		
EU RoHS Directive 2011/65/EU	Not Compliant	
EU ELV Directive 2000/53/EC	Not Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)	

Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed

Not Yet Reviewed for halogen content

Solder Process Capability

Halogen Content

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

7014AB

Time Delay Relays, Knob, 120 – 110 VAC Input, 10A@240VAC A, On-Delay, .7 – 7 seconds Delay Time, Mounting Bracket





Customers Also Bought



TE Part #2-1394765-1	TE Part #YDTS20F25-35SNV001	TE Part #2-1393127-9	TE Part #7-1393127-6
2.8FLA-STE-GEH 21P	RECP ASSY	PRD-11AY0-24=PRD	PRD-3AP4-120=PRD



Documents

Datasheets & Catalog Pages 5-1773450-5_sec12_7000

English

Instruction Sheets

Instruction Sheet (U.S.)

English

7014AB

Time Delay Relays, Knob, 120 – 110 VAC Input, 10A@240VAC A, On-Delay, .7 – 7 seconds Delay Time, Mounting Bracket

