

TE Internal #: 1445996-1

Power Contacts, Contact, 600 VAC, 600 VDC, Silver, 4 AWG Wire

Size, 21 mm² Wire Size, 41444 CMA Wire Size, Wire & Cable,

Crimp, Power, Tab

View on TE.com >



#### Connectors > Power Connectors > Power Contacts











Power Contact Type: Contact
Operating Voltage: 600 VDC

Contact Mating Area Plating Material: Silver

Wire Size: 4 AWG

## **Features**

## **Product Type Features**

| Compatible With Discrete Wire Type | Stranded     |
|------------------------------------|--------------|
| Power Contact Type                 | Contact      |
| Connector & Contact Terminates To  | Wire & Cable |

## **Electrical Characteristics**

## **Contact Features**

| Barrel Type                                    | Closed           |
|------------------------------------------------|------------------|
| Contact Mating Area Plating Material           | Silver           |
| Contact Current Rating (Max)                   | 120 A            |
| Contact Type                                   | Tab              |
| Contact Retention Within Housing               | With             |
| Mating Tab Width                               | 10.6 mm[.417 in] |
| Mating Tab Thickness                           | 4.85 mm[.191 in] |
| Contact Base Material                          | Copper Alloy     |
| Contact Mating Area Plating Material Thickness | 1.27 µm[50 µin]  |



| Wire Contact Termination Area Plating Thickness       | 50 μm[1.27 μin]            |
|-------------------------------------------------------|----------------------------|
| Wire Contact Termination Area Plating Material        | Silver                     |
| Wire Contact Termination Area Plating Material Finish | Matte                      |
| Contact Orientation                                   | Straight                   |
| Contact Underplating Material                         | Nickel                     |
| Contact Underplating Material Thickness               | 50 μm[1.27 μin]            |
| Termination Features                                  |                            |
| Termination Method to Wire & Cable                    | Crimp                      |
| Dimensions                                            |                            |
| Wire Size                                             | 41444 CMA                  |
| Usage Conditions                                      |                            |
| Operating Temperature Range                           | -40 - 105 °C[-40 - 221 °F] |
| Operation/Application                                 |                            |
| Circuit Application                                   | Power                      |
| Industry Standards                                    |                            |
| UL Rating                                             | Recognized                 |
| Agency/Standard                                       | UL                         |
| UL Flammability Rating                                | UL 94V-0                   |
| Packaging Features                                    |                            |
| Packaging Quantity                                    | 500                        |

# **Product Compliance**

Packaging Method

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                 |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC                                            |

Loose Piece



#### Free

### Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Customers Also Bought**



TE Part #211400-1 CPC PLUG ASSEMBLY SIZE 13-7



TE Part #34070 PG BUTT SPLC 22-16COMM22-18MIL



TE Part #1825059-5 ADF02ST04=DIP SWT,FLUSH,SMT-GW















## **Documents**

Product Drawings
CONTACT, 120 PWR PROD,4 AWG



## English

### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_1445996-1\_A.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1445996-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1445996-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

POWER\_CONNECTORS\_CATALOG\_SEC02\_CABLE\_MOUNTED

English

2\_PIECE\_POWER\_CONNECTORS\_qrg\_4-1773458-1

English

## **Product Specifications**

**Application Specification** 

English