

### TH/.025 Connector System

TE Internal #: 1456471-2

Housing for Female Terminals, Wire-to-Device / Wire-to-Board, 8

Position, .1 in [2.54 mm] Centerline, Black, Signal, TH/.025

Connector System

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > TH/.025 CONNECTOR SYSTEM, HOUSING











Connector System: Wire-to-Board, Wire-to-Device

Number of Positions: 8

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 2.54 mm [.1 in]

Sealable: No

All TH/.025 CONNECTOR SYSTEM, HOUSING (217)

### **Features**

### **Product Type Features**

Mixed & Hybrid Connector	Yes
Connector Shape	Rectangular
Connector System	Wire-to-Board, Wire-to-Device
Connector & Housing Type	Housing for Female Terminals
Sealable	No
Primary Locking Feature	Integrated in Housing
Configuration Features	
Number of Positions	8
Number of Rows	2
Body Features	
Cable Exit Angle	180°
Primary Product Color	Black



Connector & Keying Code	В
	D
Contact Features	
Contact Size	.64mm, 2.8mm
Contact Type	Receptacle
Mating Tab Width	.64 mm, 2.8 mm[.025 in][.11 in]
Mechanical Attachment	
Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PA GF
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Connector Height	17.67 mm[.696 in]
Product Width	24.7 mm[.972 in]
Product Length	21.42 mm[.843 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C[158 °F][167 °F][176 °F][185 °F][194 °F] [212 °F][221 °F]
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	400
Packaging Method	Box
Other	
Serviceable	No



## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts













TE Part # 1924955-1 CONTACT, FEMALEO. 64, 20-22 AWG, UNSEAL



TE Part # 1924955-3 CONTACT, FEMALEO. 64, 20-22 AWG, UNSEAL



TE Part # 1924955-5 CONTACT, FEMALE 0.64, 0.13 SQMM,



UNSEALED




TE Part # 1924955-7 CONTACT, FEMALEO. 64, 0.13 SQMM, UN



TE Part # 1924955-8 CONTACT, FEMALE, 0.64, 0.35 SQMM, UNSEALED

# Also in the Series | TH/.025 Connector System





Position Assurance(1)





Automotive Terminals(26)




Connector Seals & Cavity Plugs(2)



Insertion & Extraction Tools(4)



Other Automotive Connector Accessories(5)



PCB Headers & Receptacles(163)

# Customers Also Bought



TE Part #1452503-1 MCON 1.2 CB REC SRC SN



TE Part #1-1241930-1 AMP MCP 9.5, CONTACT



TE Part #6-1355688-5 MT3-REC. HOUSING, 10 POS.



TE Part #184139-1 WIRE SEAL, RUBBER, SENSOR, BLUE















### **Documents**

### **Product Drawings**

8p Hybrid 0.64/2.8 Unsealed Plug Assy

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1456471-2\_A\_c-1456471-2-a.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1456471-2\_A\_c-1456471-2-a.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1456471-2\_A\_c-1456471-2-a.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

TH/.025 Connector Series

English

### **Product Specifications**

**Product Specification** 

English

#### **Instruction Sheets**

Instruction Sheet (U.S.)

Housing for Female Terminals, Wire-to-Device / Wire-to-Board, 8 Position, .1 in [2.54 mm] Centerline, Black, Signal, TH/.025 Connector System



English