TE Internal #: 1551576-5

PCB Spring Contact, Preloaded - C-Clip, Scalable, Uncompressed Height 3.4 mm [.134 in], Length 3.26 mm [.128 in], Width 1.4 mm [.

055 in]

View on TE.com >



Connectors > PCB Connectors > Board-to-Board Connectors > PCB Spring Contacts











Spring Finger Type: Preloaded - C-Clip

Scalable: Yes

Side Protected: No

Uncompressed Height: 3.4 mm [.134 in]

Product Length: 3.26 mm [.128 in]

Features

Product Type Features

Spring Finger Type	Preloaded - C-Clip
Scalable	Yes
Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	

Configuration Features

Side Protected	No
Number of Positions	1

Contact Features

Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Gold
Contact Base Material	Stainless Steel
Contact Working Range (Low)	2.5 mm[.098 in]
Contact Working Range (High)	3.1 mm[.122 in]
Point of Contact Area Plating Material	Gold



Contact Current Rating (Max)	.5 A
Dimensions	
Uncompressed Height	3.4 mm[.134 in]
Product Length	3.26 mm[.128 in]
Product Width	1.4 mm[.055 in]
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Quantity	4000
Packaging Method	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



Compatible Parts





Customers Also Bought





















Documents

Product Drawings
Shield Finger, 3.4mm

English

CAD Files

Customer View Model

PCB Spring Contact, Preloaded - C-Clip, Scalable, Uncompressed Height 3.4 mm [. 134 in], Length 3.26 mm [.128 in], Width 1.4 mm [.055 in]



ENG_CVM_CVM_1551576-5_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1551576-5_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1551576-5_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English