TE Internal #: 1587826-3

Cable Seal, Silicone, Green, 4.9 mm [.192 in] Cavity Diameter, -40 –

125 °C [-40 – 257 °F] Operating Temperature

View on TE.com >



Connectors > Connector Accessories > Connector Seals & Cavity Plugs



Connector Seal & Plug Type: Cable Seal

Primary Product Material: Silicone
Primary Product Color: Green
Cavity Diameter: 4.9 mm [.192 in]
Resistance to Hydrocarbons: Poor

Features

Product Type Features

Connector Seal & Plug Type	Cable Seal
Body Features	
Primary Product Material	Silicone
Primary Product Color	Green
Housing Features	
Centerline (Pitch)	10.4 mm[.409 in]
Dimensions	
Cavity Diameter	4.9 mm[.192 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]
Packaging Features	
Packaging Quantity	500
Packaging Method	Box
Other	
Resistance to Hydrocarbons	Poor

Yes

Product Compliance

Contains Lubricant



For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought







TE Part #1587827-3 CABLE SEAL RETAINER, SIZE C, HVA280-2PI



TE Part #2307013-1 STEEL,INNER FERRULE



TE Part #2293266-4
DIA 3.6MM,PIN TERMINAL

TE Part #2066596-1 MICRO RELAY MODULE, 4P, ASSY

TE Part #2066600-1 MAXI RELAY MODULE, 2P, ASSY TE Part #2066602-1 MINIATURE FUSE MODULE, 16P, ASSY

TE Part #2297530-1 JAC S1 MAINBODY

TE Part #2350495-3 HVA280 inner ferrule

Documents

Product Drawings

CABLE SEAL, SIZE C, HVA280-2PI

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1587826-3_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1587826-3_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1587826-3_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Cable Seal, Silicone, Green, 4.9 mm [.192 in] Cavity Diameter, -40 - 125 °C [-40 - 257 °F] Operating Temperature



Application Specification

English