TE Internal #: 160337-2

Closed Ring Tongue Terminal, 18 – 14 AWG, M6 Stud Size, 6.4 mm

[.252 in] Stud Diameter, Open Barrel, Straight, Tin, Uninsulated

View on TE.com >



Terminals & Splices > Ring Terminals











Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 1618 – 4107 CMA

Stud Size: M6

## **Features**

# **Product Type Features**

| Shape Description                      | Circular/Oval               |
|--|-----------------------------|
| Ring Terminal Product Type             | Closed Ring Tongue Terminal |
| Stud Size                              | M6                          |
| Sealable                               | No                          |
| Compatible With Discrete Wire Type     | Stranded                    |
| Wire Insulation Support Retention Type | Insulation Support          |
| Configuration Features                 |                             |
| Number of Holes                        | 1                           |
| Body Features                          |                             |
| Product Weight                         | .983 g                      |
| Contact Features                       |                             |
| Contact Base Material                  | Brass                       |
| Barrel Type                            | Open                        |
| Terminal Orientation                   | Straight                    |
| Terminal Plating Material              | Tin                         |
| Contact Underplating Material          | Nickel                      |



## Mechanical Attachment

| Wire Insulation Support  | With                               |
|--|------------------------------------|
| Dimensions   |                                    |
|  | .098 in                            |
| Wire Size  | 1618 – 4107 CMA                    |
| Stud Diameter  | 6.4 mm[.252 in]                    |
| Tongue Thickness   | .51 mm[.02 in]                     |
| Product Length   | 19.81 mm[.78 in]                   |
| Barrel Inside Diameter   | 1.65 mm, 2.79 mm[.065 in][.11 in]  |
| Compatible Insulation Diameter (Max)   | .3 mm[.118 in]                     |
| Compatible Insulation Diameter Range   | 2.5 – 3 mm[.098 – .118 in]         |
| Usage Conditions   |                                    |
| Insulation Option  | Uninsulated                        |
|  |                                    |
| Operating Temperature Range  | -40 - 110 °C[-40 - 230 °F]         |
| Operating Temperature Range  Operation/Application   | -40 - 110 °C[-40 - 230 °F]         |
|  | -40 – 110 °C[-40 – 230 °F]  Copper |
| Operation/Application  |                                    |
| Operation/Application  Compatible With Wire Base Material  |                                    |
| Operation/Application  Compatible With Wire Base Material  Industry Standards                                | Copper                             |
| Operation/Application  Compatible With Wire Base Material  Industry Standards  Government Qualified Terminal | Copper                             |

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC  |



#### Free

### Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



TE Part # 160787-1 RING TONGUE IS 18-14 AWG .0840 X . 940 BR



TE Part # 62638-1 RING TONGUE 22-20 AWG TPBR



TE Part # 2151370-1 OCEAN\_2.0\_Applicator-E-130F180F




TE Part # 2151370-2 OCEAN\_2.0\_Applicator-E-130F180F












# Customers Also Bought



















### **Documents**

## **Product Drawings**

RING TONGUE IS 18-14 0.295 X .940 TPBR

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_160337-2\_H.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_160337-2\_H.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_160337-2\_H.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# **Product Specifications**

**Product Specification** 

English

**Product Specification** 

English

**Product Specification** 

English