


AMP Power Series - 120 TE Internal #: 1604001-1 Rectangular Power Connectors, Housing, Plug / Receptacle, Wireto-Wire, 1 Position, Wire & Cable, UL 94V-0, AMP Power Series - 120 View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: Housing Connector & Housing Type: Plug, Receptacle Connector System: Wire-to-Wire

Number of Positions: 1

Sealable: No

## Features

Product Type Features

Compatible With Discrete Wire Type	Stranded
Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug, Receptacle
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	1
Number of Power Positions	0
Number of Signal Positions	0
Electrical Characteristics	
Operating Voltage	600 VDC
Contact Features	
Contact Retention Within Housing	Without

## 1604001-1

Rectangular Power Connectors, Housing, Plug / Receptacle, Wire-to-Wire, 1 Position, Wire & Cable, UL 94V-0, AMP Power Series - 120



Contact Type	Blade
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Panel Mount Feature	Without
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Color	Blue
Housing Material	Polycarbonate
Dimensions	
Connector Height	69.6 mm[2.74 in]
Product Width	22.4 mm[.96 in]
Product Length	22.4 mm[.96 in]
Compatible Insulation Diameter Range	15 mm[.591 in]
Wire Size	67100 – 69073 CMA
Usage Conditions	

## **Operation/Application**

Operating Temperature Range

Circuit Application	Power
Industry Standards	
UL Rating	Recognized
Agency/Standard	UL
Approved Standards	UL E28476
UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire
Packaging Features	
Packaging Quantity	110
Packaging Method	Box
<b>Product Compliance</b> For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant

0-105 °C[32-221 °F]

**C** For support call+1 800 522 6752

## 1604001-1

Rectangular Power Connectors, Housing, Plug / Receptacle, Wire-to-Wire, 1 Position, Wire & Cable, UL 94V-0, AMP Power Series - 120



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Also in the Series | AMP Power Series - 120




# Customers Also Bought



## 1604001-1

Rectangular Power Connectors, Housing, Plug / Receptacle, Wire-to-Wire, 1 Position, Wire & Cable, UL 94V-0, AMP Power Series - 120





## Documents

## Product Drawings 120A SGL POLE HSG SUBASY, BLUE

English

**CAD** Files

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1604001-1\_C.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_1604001-1\_C.3d\_igs.zip

English

Customer View Model

### ENG\_CVM\_CVM\_1604001-1\_C.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages POWER\_CONNECTORS\_CATALOG\_SEC02\_CABLE\_MOUNTED

English

2\_PIECE\_POWER\_CONNECTORS\_qrg\_4-1773458-1

English

Product Specifications Application Specification

English