# 3100-1502999 ! PENDING OBSOLESCENCE

### Products Unlimited | Products Unlimited 3100

TE Internal #: 1611001-3 TE Internal Description: 3100-15Q2999=30A 1PWS 24V PROD DP Contactors, 1 Pole

#### View on TE.com >



Relays, Contactors & Switches > Contactors > Definite Purpose Contactors > DP Contactors, 1 Pole



### Pole Configuration: 1

Definite Purpose Contactor Coil Voltage Rating: 24 VAC

Definite Purpose Contactor Contact Current Rating: 30 A

Definite Purpose Contactor Mounting Type: Panel

Definite Purpose Contactor Contact Arrangement: 1 Form X, SPST-NO-DM with Shunt

#### All DP Contactors, 1 Pole (0)

### Features

### **Product Type Features**

| Molded   | No                         |
|--|----------------------------|
| Product Category   | Electromechanical Relays   |
| Product Type   | Contactor                  |
| Arc Cover  | Without                    |
| Product Classification                                     | Relays - Contactors        |
| Model  | 96                         |
| Contactor Type   | Definite Purpose           |
| Terminal Configuration                                     | 10-32 Screw, Quick Connect |
| Electrical Characteristics                                 |                            |
| Actuating System   | AC                         |
| Coil Voltage (Max)   | 24 VAC                     |
| Definite Purpose Contactor Coil Voltage Rating             | 24 VAC                     |
| Definite Purpose Contactor Coil Resistance                 | 16.5 Ω                     |
| Definite Purpose Contactor Contact Switching Voltage (Max) | 600 VAC                    |
| Contact Features   |                            |
| Contact Base Material                                      | Silver Cadmium Oxide       |
| Pole Configuration   | 1                          |
|  |                            |

**C** For support call+1 800 522 6752

### 3100-1502999

#### 3100-15Q2999=30A 1PWS 24V PROD



| Definite Purpose Contactor Contact Current Rating | 30 A   |
|---|--|
| Definite Purpose Contactor Contact Arrangement    | 1 Form X, SPST-NO-DM with Shunt                  |
| Termination Features                              |  |
| Coil Termination                                  | Quick Connect                                    |
| Mechanical Attachment                             |  |
| Mounting Plate                                    | With   |
| Definite Purpose Contactor Mounting Type          | Panel  |
| Dimensions  |  |
| Wire Size   | 1.31 – 8.37 mm <sup>2</sup>                      |
| Industry Standards                                |  |
| UL Flammability Rating                            | UL 94V-0   |
| Agency Approval                                   | CSA Certified, SEMKO Certified, UL<br>Recognized |
| Packaging Features                                |  |
| Packaging Method                                  | Loose Piece                                      |
| Other   |  |
| Comment   | Stranding must be split for 8 AWG wire.          |

Torque

25 in-lbs

# Product Compliance

### For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant with Exemptions  |
|---|--|
| EU ELV Directive 2000/53/EC                   | Not Compliant  |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023<br>(235)<br>Candidate List Declared Against: JUNE<br>2022 (224)<br>SVHC > Threshold:<br>Cadmium oxide (10.81% in Component<br>Part)<br>Article Safe Usage Statements:<br>Use personal protective equipment as required. Do not eat, drink or smoke when<br>using this product. Recycle if possible and dispose of the article by following all<br>applicable governmental regulations relevant to your geographic location. |
| Halogen Content                               | Not Yet Reviewed for halogen content   |
| Solder Process Capability                     | Not applicable for solder process capability   |

**C** For support call+1 800 522 6752

#### 3100-15Q2999=30A 1PWS 24V PROD



#### Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



# Also in the Series | Products Unlimited 3100





# Customers Also Bought



### Documents

### CAD Files 3D PDF

**&** For support call+1 800 522 6752

3100-15Q2999



3D

Customer View Model ENG\_CVM\_CVM\_1611001-3\_C.2d\_dxf.zip English

Customer View Model

ENG\_CVM\_CVM\_1611001-3\_C.3d\_igs.zip

English

Customer View Model ENG\_CVM\_CVM\_1611001-3\_C.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages Model 96 - 3100 Definite Purpose Contactor 1- or 2-pole, 20-40 FLA AC Coil

English

## Product Specifications Definitions General Purpose Relays

English