



Passive Components > Resistors > Through-Hole Resistors > Wirewound Resistor: Vertical Mount



Resistor Type: **Power Resistor**
Passive Component Dimensions: **75 x 10 x 9 mm**
Number of Terminations: **2**
Packaging Method: **Loose Piece - Box**
Passive Component Tolerance: **5 %**

[All Wirewound Resistor: Vertical Mount \(166\)](#)

Features

Product Type Features

Product Type	Fixed Resistor
Resistor Type	Power Resistor
Element Type	Wire Wound

Configuration Features

Number of Resistors	1
---------------------	---

Electrical Characteristics

Passive Component Tolerance	5 %
Resistance Class	1k Ω – 1M Ω
Resistance Value	1.5K Ω
Power Rating	17 W

Body Features

Passive Component Lead Type	Axial-Leaded
-----------------------------	--------------

Termination Features

Number of Terminations	2
Passive Component Termination Material Type	Tinned Copper Leads

Dimensions

--



Passive Component Dimensions	75 x 10 x 9 mm
------------------------------	----------------

Usage Conditions

Operating Temperature Range	-55 – 350 $^{\circ}\text{C}$
Temperature Coefficient	± 200 ppm/ $^{\circ}\text{C}$

Packaging Features

Packaging Method	Loose Piece - Box
------------------	-------------------

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265 $^{\circ}\text{C}$

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

SBCHE151K5J

1.5K Ω , Wire Wound, Power Resistor, 5 %, 75 x 10 x 9 mm, 2 Termination, Loose Piece
- Box, 17 W, ± 200 ppm/ $^{\circ}\text{C}$, Tinned Copper Leads Termination, CGS SBC



TE Part # CAT-C339-SB19B
Wirewound Resistor: Vertical Mount

TE Part # 1623728-3
BCHE 11 W 10R 5%

Also in the Series | CGS SBC

Surface Mount Resistors(1)

Through-Hole Resistors(212)

Customers Also Bought

TE Part #1623728-7
BCHE 11 W 1K0 5%

TE Part #7-215079-6
Female-on-Board Connector, Top Entry

TE Part #1-1623788-3
Wirewound Resistor: Vertical Mount

TE Part #T4110002081-000
M12,FEMALE,STRAIGHT,A CODE,8P, PG9,GOLD

TE Part #3-1761608-1
IDC LOW PRO HDR 34P VERT SHT L

TE Part #2-215882-6
26 WAY GREY MK II RECP

TE Part #2-1761608-6
IDC LOW PRO HDR 16P VERT SHT L

TE Part #1-1337450-0
BNC BHSkt + TAG 50Ohm Silver Pltd

Documents

Product Drawings
BCHE 17 W 1K5 5%

English

Datasheets & Catalog Pages
4-1773460-6_RESISTIVE_SOLUTIONS_RAIL

English

SBCHE151K5J

1.5K Ω , Wire Wound, Power Resistor, 5 %, 75 x 10 x 9 mm, 2 Termination, Loose Piece
- Box, 17 W, ± 200 ppm/ $^{\circ}\text{C}$, Tinned Copper Leads Termination, CGS SBC



1309350_PASSIVE_COMPONENT

English

High Power Resistor - Type SBC (Square Ceramic) Series - Tyco Electronics Passives

English

8-1773459-4_POWER_FILTERING_AND_RESISTIVE_SOLUTIONS_FOR_ELEVATORS_AND_ESCALATORS

English