SC30100KT <

Sigma | Sigma SC TE Internal #: 1624000-3 10 μH, Radio Frequency Inductor, 219 mA, 3.7 Ω DC Resistance, Axial-Leaded, Wire Wound, 10 %, 7 x 2.8 mm, Ammo Packed, Through Hole - Solder, Sigma SC

View on TE.com >



Passive Components > Inductors > High Frequency & RF Inductors



Inductor Type: Radio Frequency

Termination Method to Printed Circuit Board: Through Hole - Solder

Packaging Method: Ammo Packed

Passive Component Dimensions: 7 x 2.8 mm

Passive Component Tolerance: 10 %

Features

Product Type Features

Inductor Type

Element Type

Radio Frequency

Wire Wound

Electrical Characteristics

| Self Resonant Frequency | .05 GHz | |
|---|-----------------------|--|
| Passive Component Tolerance | 10 % | |
| Inductance | 10 μΗ | |
| Current Rating (Max) | 219 mA | |
| DC Resistance | 3.7 Ω | |
| Body Features | | |
| Passive Component Lead Type | Axial-Leaded | |
| Termination Features | | |
| Termination Method to Printed Circuit Board | Through Hole - Solder | |
| Dimensions | | |
| Passive Component Dimensions | 7 x 2.8 mm | |
| Usage Conditions | | |
| Operating Temperature Range | -55 – 100 °C | |
| Packaging Features | | |
| | | |

C For support call+1 800 522 6752

09/27/2023 10:32AM | Page 1

SC30100KT

10 μ H, Radio Frequency Inductor, 219 mA, 3.7 Ω DC Resistance, Axial-Leaded, Wire Wound, 10 %, 7 x 2.8 mm, Ammo Packed, Through Hole - Solder, Sigma SC



| Packaging Method | Ammo Packed |
|---|---|
| Other | |
| Inductor Quality Factor | 55 |
| Product Compliance For compliance documentation, visit the product page on TE.com> | |
| EU RoHS Directive 2011/65/EU | Compliant |
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
| Halogen Content | Not Yet Reviewed for halogen content |
| Solder Process Capability | Wave solder capable to 265°C |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



SC30100KT

10 μH, Radio Frequency Inductor, 219 mA, 3.7 Ω DC Resistance, Axial-Leaded, Wire Wound, 10 %, 7 x 2.8 mm, Ammo Packed, Through Hole - Solder, Sigma SC



TE Part # 1624019-2 SC30-10-2531-10 33UH AMMO 1000

Also in the Series | Sigma SC



Customers Also Bought



| | STATOGO SU LA | | |
|------------------------|----------------------------|--------------------------|----------------------|
| TE Part #5747497-4 | TE Part #1-1462039-8 | TE Part #1462051-4 | TE Part #3-1625963-9 |
| 50 PLUG RA/MS STD (SL) | IM06DGR=IM RELAY 140mW 12V | HF356=50OHM140MW12V MONO | HSA5 5R0 1% |



Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1624000-3_BA.2d_dxf.zip

English

SC30100KT

10 μ H, Radio Frequency Inductor, 219 mA, 3.7 Ω DC Resistance, Axial-Leaded, Wire Wound, 10 %, 7 x 2.8 mm, Ammo Packed, Through Hole - Solder, Sigma SC



Customer View Model

ENG_CVM_CVM_1624000-3_BA.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_1624000-3_BA.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages 1309350_PASSIVE_COMPONENT

English

Axial Leaded Power Inductors - Type SC10, SC15, SC30 Series - Tyco Electronics Passives

English