

Alcoswitch

TE Internal #: 1634201-2

Rocker Switches, Power, Panel Cutout Size 1.19 x .874 in [30.2 x 22.2 mm], Silver Tin Oxide, Double Pole - Single Throw Configuration

(Pole-Throw)
View on TE.com >



Relays, Contactors & Switches > Switches > Rocker Switches











Rocker Switch Type: Power

Rocker Switch Mounting Type: Panel

Indicator/Imprint Legend: O -

Panel Cutout Size: 30.2 x 22.2 mm [1.19 x .874 in]
Switch Contact Plating Material: Silver Tin Oxide

Features

Product Type Features

Product Type	Switch
Rocker Switch Type	Power
Lamp	Without
Rocker Switch LED	Without
Actuator Type	Тор
Actuator Style	Rocker

Configuration Features

Indicator/Imprint Color	White
Indicator/Imprint Legend	O -
Panel Cutout Size	30.2 x 22.2 mm[1.19 x .874 in]
Configuration (Pole-Throw)	Double Pole - Single Throw
Operating Function	On Off

Electrical Characteristics

Rocker Switch Voltage Rating 125 VAC, 250 VAC



Body Features

Beveled Frame Color	Black
Body Color	Black
Actuator Color	Black

Contact Features

Terminal Tab Width	6.35 mm[.25 in]
Switch Contact Plating Material	Silver Tin Oxide
Rocker Switch Contact Current Rating	10 A, 16 A

Termination Features

Termination Type	Quick Connect

Mechanical Attachment

Mounting Angle	Vertical
Rocker Switch Mounting Type	Panel

Housing Features

Process Sealed	No
----------------	----

Industry Standards

VDE Tested	Yes	
------------	-----	--

Other

Comment Dust Resis	tant., Non-Illuminated

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



PRFDA1-16F-BB000



TE Part # 1634201-3 PRFDA1-16F-BB0CW



TE Part # 1634201-4 PRFDB1-16F-BR000



TE Part # 1-1634201-2 PRFDD3-16F-BB0GW







Customers Also Bought





















Documents

Product Drawings

PRFDA1-16F-BB0BW

English

CAD Files

Customer View Model

ENG_CVM_CVM_1634201-2_E.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1634201-2_E.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_1634201-2_E.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

SWITCHES_CORE_PROGRAM_CATALOG

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

Rocker Switches, Power, Panel Cutout Size 1.19 \times .874 in [30.2 \times 22.2 mm], Silver Tin Oxide, Double Pole - Single Throw Configuration (Pole-Throw)

