1658391-2 ACTIVE

SFP28

TE Internal #: 1658391-2

SFP, SFP+ & zSFP+, Cage Assembly with Integrated Connector,

Data Rate (Max) 4 Gb/s, Internal/External EMI Springs, SFP, Not

Optional, 2 x 1

View on TE.com >



Connectors > Pluggable IO Connectors & Cages > SFP, SFP+ & zSFP+ > SFP+ Stacked Cage Assemblies











Pluggable I/O Product Type: Cage Assembly with Integrated Connector

Data Rate (Max): 4 Gb/s

EMI Containment Feature Type: Internal/External EMI Springs

Pluggable I/O Applications: **SFP**Lightpipe Options: **Not Optional**

All SFP+ Stacked Cage Assemblies (122)

Features

Product Type Features

| Form Factor | SFP |
|-----------------------------------|---|
| Cage Type | Stacked |
| Pluggable I/O Product Type | Cage Assembly with Integrated Connector |
| Lightpipe Options | Not Optional |
| Connector System | Cable-to-Board |
| Sealable | No |
| Connector & Contact Terminates To | Printed Circuit Board |
| | |

Configuration Features

| Port Matrix Configuration | 2 x 1 |
|---------------------------|-------|
| Number of Ports | 2 |
| Number of Positions | 40 |

Electrical Characteristics



| Data Rate (Max) | 4 Gb/s |
|---|-------------------------------|
| Contact Features | |
| Contact Current Rating (Max) | .5 A |
| Termination Features | |
| Termination Method to Printed Circuit Board | Through Hole - Press-Fit |
| Mechanical Attachment | |
| Connector Mounting Type | Board Mount |
| Housing Features | |
| Centerline (Pitch) | .8 mm[.03 in] |
| Usage Conditions | |
| Operating Temperature Range | -55 – 105 °C[-67 – 221 °F] |
| Operation/Application | |
| Pluggable I/O Applications | SFP |
| Circuit Application | Signal |
| Other | |
| EMI Containment Feature Type | Internal/External EMI Springs |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
| Halogen Content | Not Low Halogen - contains Br or Cl > 900 ppm. |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Customers Also Bought

















Documents

Product Drawings

SFP CAGE&PT ASSY PRESS FIT 2X1

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1658391-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1658391-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1658391-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Product Specifications

SFP, SFP+ & zSFP+, Cage Assembly with Integrated Connector, Data Rate (Max) 4 Gb /s, Internal/External EMI Springs, SFP, Not Optional, 2 x 1



Application Specification

English

Product Environmental Compliance

Product Compliance Document

English

Product Compliance Document

English