


FASTON | FASTON 250

TE Internal #: 170267-1 PCB Terminals, Tab, Mating Tab Width .25 in [6.35 mm], PCB Hole Diameter 1.4 mm [.055 in], Through Hole - Solder, Tin Plating, Copper, Bag, FASTON 250

View on TE.com >

Terminals & Splices > PCB Terminals



PCB Terminal Type: Tab

PCB Thickness (Recommended): 1.57 – 2.39 mm [.062 – .093 in]

Mating Tab Width: 6.35 mm [.25 in]

Mating Tab Thickness: .81 mm [.032 in]

PCB Hole Diameter: 1.4 mm [.055 in]

Features



Product Type Features

Insertion Force	Low
Contact Features	
PCB Contact Termination Area Plating Material Thickness	3.81 μm[150 μin]
Contact Underplating Material Thickness	1.3 μm[51.18 μin]
Contact Mating Area Plating Material Thickness	3.81 μm[150 μin]
PCB Terminal Type	Tab
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Plating Material	Tin
Contact Underplating Material	Copper
Terminal Size	6.35
Terminal Orientation	Straight
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Solder

C For support call+1 800 522 6752

PCB Terminals, Tab, Mating Tab Width .25 in [6.35 mm], PCB Hole Diameter 1.4 mm [. 055 in], Through Hole - Solder, Tin Plating, Copper, Bag, FASTON 250



Product Terminates To	Printed Circuit Board
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
PCB Thickness (Recommended)	1.57 – 2.39 mm[.062 – .093 in]
PCB Hole Diameter	1.4 mm[.055 in]
Profile Height from PCB	9.6 mm[.382 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Packaging Features	
Packaging Quantity	1000
	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU

Compliant

EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on

PCB Terminals, Tab, Mating Tab Width .25 in [6.35 mm], PCB Hole Diameter 1.4 mm [. 055 in], Through Hole - Solder, Tin Plating, Copper, Bag, FASTON 250




requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts





Also in the Series | FASTON 250



Customers Also Bought

PCB Terminals, Tab, Mating Tab Width .25 in [6.35 mm], PCB Hole Diameter 1.4 mm [. 055 in], Through Hole - Solder, Tin Plating, Copper, Bag, FASTON 250





Documents

Product Drawings 250 FASTON,PCB TAB,TCBR

English

CAD Files 3D PDF

3D

Customer View Model ENG_CVM_CVM_170267-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_170267-1_B.3d_igs.zip

English

Customer View Model

```
ENG_CVM_CVM_170267-1_B.3d_stp.zip
```

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Environmental Compliance MD_170267-1_12182017142_dmtec

English

```
MD_170267-1_12182017142_dmtec
```

English

Agency Approvals CSA Certificate

English

PCB Terminals, Tab, Mating Tab Width .25 in [6.35 mm], PCB Hole Diameter 1.4 mm [. 055 in], Through Hole - Solder, Tin Plating, Copper, Bag, FASTON 250

