

FASTIN-FASTON | FASTIN-FASTON 375

TE Internal #: 171447-3

Crimp Terminal Housings, Receptacle, Receptacle, 2 Position, Straight, Brown, Nylon, Contact Mating Retention, Mating

Alignment, FASTIN-FASTON 375

View on TE.com >




Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings











Terminal Type: Receptacle

Connector & Housing Type: Receptacle

Number of Positions: 2

Terminal Orientation: Straight
Primary Product Color: Brown

Features

Product Type Features

Sealable	No
Connector & Contact Terminates To	Wire & Cable
Connector & Housing Type	Receptacle
Configuration Features	
Number of Positions	2
Body Features	
Primary Product Color	Brown
Contact Features	
Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	With
Mechanical Attachment	

Latch

Mating Retention Type



Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	Nylon
Centerline (Pitch)	12.3 mm[.484 in]
Dimensions	
Product Length	33 mm[1.3 in]
Usage Conditions	
Operating Temperature Range	-40 – 150 °C[-40 – 302 °F]
Packaging Features	
Packaging Quantity	500

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach




Compatible Parts



Also in the Series | FASTIN-FASTON 375



Customers Also Bought



Documents

Product Drawings
FF 375 PLUG HSG 2P NYLON BROWN

English

CAD Files



3D PDF

3D

Customer View Model

ENG_CVM_CVM_171447-3_D_c-171447-3-d.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_171447-3_D_c-171447-3-d.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_171447-3_D_c-171447-3-d.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

White Paper: Nylon Discoloration

English

Product Specifications

Application Specification

English