




Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Plug**

Connector System: **Wire-to-Board**

Number of Positions: **2**

Centerline (Pitch): **3.96 mm [.156 in]**

Features

Product Type Features

Header Type	Partially Shrouded
Rectangular Power Connector Type	Header
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	2
PCB Mount Orientation	Vertical
Number of Power Positions	2
Number of Rows	1

Electrical Characteristics

Operating Voltage	250 VDC
-------------------	---------

Contact Features



Mating Post Length	7.7 mm[.303 in]
PCB Contact Termination Area Plating Material Thickness	3 µm[120 µin]
Contact Layout	Inline
Contact Mating Area Plating Material	Tin
Contact Base Material	Brass
Contact Current Rating (Max)	8 A
Contact Retention Within Housing	Without
Contact Type	Pin
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	3.05 µm[120 µin]

Termination Features

Termination Post & Tail Length	3.69 mm[.145 in]
Termination Method to Printed Circuit Board	Through Hole - Solder

Mechanical Attachment

PCB Mount Alignment Type	Boss
Strain Relief	Without
Mating Retention	With
Mating Alignment	Without
PCB Mount Alignment	With
PCB Mount Retention	Without
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	3.96 mm[.156 in]
Housing Color	Natural
Housing Material	Nylon

Dimensions

Connector Height	9.4 mm[.37 in]
Product Length	7.92 mm[.312 in]

Usage Conditions

Operating Temperature Range	-25 – 105 °C[-13 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------



Industry Standards

UL Flammability Rating	UL 94V-0
Glow Wire Rating	GWT 750°C (Without Flame)

Packaging Features

Packaging Quantity	1000
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1-1123722-2
3.96 EP PLUG HSG 2P(NATURAL)

TE Part # 1744544-2
EP II TPA 02P, BLACK

TE Part # 1-1744429-6
3.96 EP HDR ASSY 6P W/PEGS, GW, NO PIN 3

TE Part # 1-1744429-9
3.96 EP HDR ASSY 9P W/PEGS, GW, NO PIN 3

TE Part # 1-1744524-0
EP 10P HEADER ASY NO 8 PIN

TE Part # 1-1744524-1
EP 11P HEADER ASY NO 6,10 PINS

TE Part # 1-1744524-2
EP 12P HEADER ASY NO 2,6 PINS

TE Part # 2-1744435-8
EP 08P V-HDR ASY NO 3 PIN

TE Part # 2-1744524-5
EP 05P HEADER ASY NO 2,3,4 PIN

Also in the Series | Economy Power

Connector Contacts(1)

Insertion & Extraction Tools(1)

PCB Headers & Receptacles(162)


PCB Latches, Locks & Retainers(2)

Power Contacts(8)

Rectangular Connector Housings(1)


Rectangular Power Connectors(302)

Wire-to-Board Connector Assemblies & Housings(142)




Wire-to-Board Connector Contacts(6)


Customers Also Bought



TE Part #796634-4
4 POS 5.08MM R/A PLUG,TRM BLK



TE Part #1586040-2
2P VAL-U-LOK VRT HDR W/P V0




TE Part #2029056-3
3P VAL-U-LOK SR HDR SN V0 W/DH



TE Part #4-1123724-2
3.96EP HDR ASSY 2(3)P RED



TE Part #4-1393210-3
T9AV1D12-12U



TE Part #1775317-4
HPL,2.5MM PITCH,V/T,SMT TYPE,4 POS



TE Part #1744429-8
3.96 EP HDR ASSY 8P W/PEGS, GW



TE Part #2-2322950-5
5P, RAST 5 TAB HEADER SELEC, THV, OPP



TE Part #2322950-4
4P, RAST 5 TAB HEADER SELEC, THV, OPP



TE Part #6-1565036-5
EP CONN. HDR ASSY 5/6P W/O#5 BLUE

Documents

Product Drawings

3.96 EP HDR ASSY 2P W/PEGS, GW

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1744429-2_D.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_1744429-2_D.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1744429-2_D.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[Economy Power II \(EP II\) Glow Wire test compliant connectors](#)

English

[1-1773885-9 Economy Power Connectors](#)

English

Product Specifications

[Application Specification](#)

Japanese

Product Environmental Compliance

[MD_1744429-2_100820152350_dmtec](#)

English

[MD_1744429-2_100820152350_dmtec](#)

English