

Economy Power 2.5

TE Internal #: 1744446-6

PCB Mount Header, Right Angle, Wire-to-Board, 6 Position, 2.5 mm [.098 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder,

Economy Power 2.5

View on TE.com >




Connectors > PCB Connectors > PCB Headers & Receptacles











Connector System: Wire-to-Board

Number of Positions: 6
Number of Rows: 1

Centerline (Pitch): 2.5 mm [.098 in]
PCB Mount Orientation: Right Angle

Features

Product Type Features

Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header
Configuration Features	
Number of Positions	6
Number of Rows	1
PCB Mount Orientation	Right Angle
Electrical Characteristics	
Operating Voltage	250 VAC
Body Features	

Natural

Primary Product Color



Contact Features

PCB Contact Termination Area Plating Material Thickness	2.032 µm[80 µin]
Contact Layout	Inline
Mating Pin Diameter	.6 mm[.024 in]
Contact Mating Area Plating Material Thickness	2 – 5 μm[80 – 200 μin]
PCB Contact Termination Area Plating Material Finish	Bright
Contact Mating Area Plating Material Finish	Bright
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Tin
Contact Type	Pin
Contact Current Rating (Max)	4.2 A

Termination Features

Round Termination Post & Tail Diameter	.6 mm[.024 in]
Termination Post & Tail Length	3.2 mm
Termination Method to Printed Circuit Board	Through Hole - Solder

Mechanical Attachment

Mating Alignment TypePolarizationMating RetentionWithPanel Mount FeatureWithoutPCB Mount Retention TypeKinkedMating Retention TypeLatchConnector Mounting TypeBoard MountMating AlignmentWithPCB Mount AlignmentWithPCB Mount RetentionWith	PCB Mount Alignment Type	Boardlock
Panel Mount Feature PCB Mount Retention Type Kinked Mating Retention Type Latch Connector Mounting Type Board Mount Mating Alignment With PCB Mount Alignment With	Mating Alignment Type	Polarization
PCB Mount Retention Type Kinked Mating Retention Type Latch Connector Mounting Type Board Mount Mating Alignment With PCB Mount Alignment With	Mating Retention	With
Mating Retention Type Latch Connector Mounting Type Board Mount Mating Alignment With PCB Mount Alignment With	Panel Mount Feature	Without
Connector Mounting Type Board Mount With PCB Mount Alignment With	PCB Mount Retention Type	Kinked
Mating Alignment PCB Mount Alignment With With	Mating Retention Type	Latch
PCB Mount Alignment With	Connector Mounting Type	Board Mount
	Mating Alignment	With
PCB Mount Retention With	PCB Mount Alignment	With
	PCB Mount Retention	With

Housing Features

Housing Material	Nylon
Centerline (Pitch)	2.5 mm[.098 in]

Dimensions

	7.5. [205 :]
Connector Length	7.5 mm[.295 in]



Connector Height	7.6 mm[.299 in]
Connector Width	12.6 mm[.496 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Glow Wire Rating	Glow Wire
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	450

Box

Product Compliance

Packaging Type

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



Compatible Parts





Also in the Series | Economy Power 2.5



PCB Headers & Receptacles(494)




PCB Latches, Locks & Retainers(49)



Rectangular Power Connectors(43)



Wire-to-Board Connector Assemblies & Housings(311)



Customers Also Bought





















Documents

Product Drawings

Hdr Assy, EP 2.5 RA, 6 Pos., GW

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1744446-6_H.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1744446-6_H.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1744446-6_H.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

7-1773461-6_EP2.5_Connector_Series

English

Product Specifications

Application Specification

English

Product Environmental Compliance

TE Material Declaration

PCB Mount Header, Right Angle, Wire-to-Board, 6 Position, 2.5 mm [.098 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, Economy Power 2.5



English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

UL Report

English