TE Internal #: 1811027-2

Splices, Tap Splice, 18 AWG Wire Size, Strain Relief, Copper Alloy, Blue, Length .965 in [24.5 mm], Loose Piece, Stranded / Solid Wire,

Copper Wire

View on TE.com >



Terminals & Splices > Splices











Wire Size: 18 AWG

Sealable: No

Splice Features: Strain Relief

Compatible Insulation Diameter Range: 2.3 mm

Contact Base Material: Copper Alloy

## **Features**

# Product Type Features

Sealable	No
Splice Type	Tap Splice
Compatible With Discrete Wire Type	Solid, Stranded
Configuration Features	
Compatible With Wire & Cable Type	Discrete Wire
Electrical Characteristics	
Operating Voltage	600 VAC
Body Features	
Splice Features	Strain Relief
Primary Product Color	Blue
Contact Features	
Terminal Plating Thickness	9 μm[354.33 μin]

Bright Tin

Copper Alloy

Terminal Plating Material

Contact Base Material



## Mechanical Attachment

Wire Insulation Support	Without
Housing Features	
Housing Material	Thermoplastic
Dimensions	
Wire Size	18 AWG
Compatible Insulation Diameter Range	2.3 mm
Product Length	24.5 mm[.965 in]
Usage Conditions	
Insulation Option	Fully Insulated
Operating Temperature Range	-55 – 105 °C
Operation/Application	
Operation/Application  Compatible With Wire Base Material	Copper
	Copper
Compatible With Wire Base Material	Copper CSA, UL
Compatible With Wire Base Material  Industry Standards	
Compatible With Wire Base Material  Industry Standards  Agency/Standard	CSA, UL
Compatible With Wire Base Material  Industry Standards  Agency/Standard  Approved Standards	CSA, UL CSA C22.2 No. 189, UL 486C
Compatible With Wire Base Material  Industry Standards  Agency/Standard  Approved Standards  UL Flammability Rating	CSA, UL  CSA C22.2 No. 189, UL 486C  UL 94V-0
Compatible With Wire Base Material  Industry Standards  Agency/Standard  Approved Standards  UL Flammability Rating  Government Qualified Splice	CSA, UL  CSA C22.2 No. 189, UL 486C  UL 94V-0

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.



## Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





# Customers Also Bought























### **Documents**

# **Product Drawings**

ASSEMBLY,18AWG TAP

English

#### **CAD Files**

3D PDF

English

**Customer View Model** 

ENG\_CVM\_1811027-2\_A1.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_1811027-2\_A1.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_1811027-2\_A1.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1811027-2\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1811027-2\_B.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1811027-2\_B.2d\_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

Poke-in Wire tap IDC Splice flyer

Poke-in Wire tap IDC Splice flyer

English

**Product Specifications** 

Splices, Tap Splice, 18 AWG Wire Size, Strain Relief, Copper Alloy, Blue, Length .965 in [24.5 mm], Loose Piece, Stranded / Solid Wire, Copper Wire



**Application Specification** 

English

**Instruction Sheets** 

Instruction Sheet (U.S.)

English

Agency Approvals

Agency Approval Document

English