1813139-1 ✓ ACTIVE

Micro Timer II

TE Internal #: 1813139-1

Plug, Wire-to-Board / Wire-to-Wire / Wire-to-Device, 6 Position, .


157 in [4 mm] Centerline, Sealable, Black, Wire & Cable, Signal,

Micro Timer II

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > Timer Connector Housing



Connector System: Wire-to-Board, Wire-to-Device, Wire-to-Wire

Number of Positions: 6

Connector & Housing Type: Plug Centerline (Pitch): 4 mm [.157 in]

Sealable: Yes

All Timer Connector Housing (585)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Board, Wire-to-Device, Wire-to- Wire
Connector & Housing Type	Plug
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	6
Number of Rows	2
Body Features	
Cable Exit Angle	180°
Primary Product Color	Black
Connector & Keying Code	1
Contact Features	
Contact Size	1.6mm



Contact Type	Receptacle
Mating Tab Width	1.6 mm[.063 in]
Mechanical Attachment	
Terminal Position Assurance	Yes
Strain Relief	Add By Accessory
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PBT
Centerline (Pitch)	4 mm[.157 in]
Dimensions	
Connector Height	31.4 mm[1.236 in]
Product Width	25.1 mm[.988 in]
Product Length	25.5 mm[1.004 in]
Row-to-Row Spacing	2.54 mm[.1 in]
Operation/Application	
Circuit Application	Signal
Industry Standards	
Degree of Protection	IP6K9K
UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	100
Packaging Method	Bag
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts



Also in the Series | Micro Timer II



Automotive Connector Caps & Covers (2)



Automotive Connector Locks & Position Assurance(1)




Automotive Housings(34)



Automotive Terminals(30)





Customers Also Bought

















Documents

Product Drawings

SEALED MT2 6POSN PLUG HOUSING ASSEMBLY

English

CAD Files

Customer View Model

ENG_CVM_CVM_1813139-1_O1.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1813139-1_O1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1813139-1_O1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Plug, Wire-to-Board / Wire-to-Wire / Wire-to-Device, 6 Position, .157 in [4 mm] Centerline, Sealable, Black, Wire & Cable, Signal, Micro Timer II



Datasheets & Catalog Pages
Timer Interconnection System

English