

CGS | CGS TE

TE Internal #: 1879449-5

 2.2Ω , Wire Wound, Power Resistor, $326 \times 40 \times 81 \text{ mm}$, 2

Termination, Loose Piece - Box, 5 %, 400 W, ±440 ppm/°C, Solder

Lug Termination, CGS TE

View on TE.com >



Passive Components > Resistors > Chassis Mount Resistors > Wirewound Resistor: Mineral, 2.5 Kw



Resistor Type: Power Resistor

Passive Component Dimensions: 326 x 40 x 81 mm

Number of Terminations: 2

Packaging Method: Loose Piece - Box
Passive Component Tolerance: 5 %

All Wirewound Resistor: Mineral, 2.5 Kw (685)

Features

Product Type Features

Resistor Type	Power Resistor
Element Type	Wire Wound
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Voltage Rating	2500 V
Passive Component Tolerance	5 %
Resistance Class	Up to $1k\Omega$
Resistance Value	2.2 Ω
Power Rating	400 W
Termination Features	
Number of Terminations	2
Chassis Mount Resistor Termination Type	Solder Lug

Bracket

Mechanical Attachment

Chassis Mount Resistor Mount Style



Passive Component Dimensions	326 x 40 x 81 mm
Usage Conditions	
Operating Temperature Range	-55 – 155 °C
Temperature Coefficient	±440 ppm/°C
Packaging Features	
Packaging Method	Loose Piece - Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | CGS TE






RJ11 Connectors(1)









Customers Also Bought





Documents

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_1879449-5_BB.2d_dxf.zip

English

 $2.2~\Omega$, Wire Wound, Power Resistor, 326~x~40~x~81 mm, 2 Termination, Loose Piece - Box, 5~%, 400~W, $\pm440~ppm/^{\circ}C$, Solder Lug Termination, CGS TE



Customer View Model

ENG_CVM_CVM_1879449-5_BB.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1879449-5_BB.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

4-1773460-6_RESISTIVE_SOLUTIONS_RAIL

English

1309350_PASSIVE_COMPONENT

English

8-1773459-4_POWER_FILTERING_AND_RESISTIVE_SOLUTIONS_FOR_ELEVATORS_AND_ESCALATORS

English

High Power Wire wound Resistor Type TE Series

English