

#### MULTI-BEAM

TE Internal #: 1892801-1 Rectangular Power Connectors, Connector Assembly, Plug, Boardto-Board, 18 Position, 6.35 mm / 2.54 mm [.1 in / .25 in] Centerline View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



# Rectangular Power Connector Type: Connector Assembly Connector & Housing Type: Plug

Connector System: Board-to-Board

Number of Positions: 18

Centerline (Pitch): 2.54 mm, 6.35 mm [.1 in, .25 in]

## Features

### **Product Type Features**

Assembly Requirement	Factory Assembled
Rectangular Power Connector Type	Connector Assembly
Connector & Housing Type	Plug
Connector System	Board-to-Board

Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Mating & Unmating Configuration	Normal
Number of Positions	18
PCB Mount Orientation	Vertical
Number of Power Positions	2
Number of Signal Positions	16
Number of Rows	4
Electrical Characteristics	
Operating Voltage	60 VDC, 200 VDC
Body Features	
Wire Color (Base)	Black
Contact Features	
Power Contact Base Material	Tin

## 1892801-1

Rectangular Power Connectors, Connector Assembly, Plug, Board-to-Board, 18 Position, 6.35 mm / 2.54 mm [.1 in / .25 in] Centerline



Contact Underplating Material Thickness	4.19 µm
Contact Mating Area Plating Material	Gold
Contact Current Rating (Max)	50 A
Contact Retention Within Housing	Without
Contact Type	Blade, Pin
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
ermination Features	
Termination Post & Tail Length	4.19 mm[.165 in]
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Aechanical Attachment	
PCB Mount Retention	With
PCB Mount Retention Type	Boardlock
Mating Retention Type	Boardlock
Connector Mounting Type	Board Mount
lousing Features	
Centerline (Pitch)	2.54 mm, 6.35 mm[.1 in][.25 in]
Housing Color	Black
Housing Material	Thermoplastic
Dimensions	
Row-to-Row Spacing	.1 mm[.003 in]
Jsage Conditions	
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Operation/Application	
Circuit Application	Power & Signal
ndustry Standards	
UL Flammability Rating	UL 94V-0
Glow Wire Rating	High Temperature Part - Not Glow Wire
Packaging Features	
Packaging Method	Tray

# Product Compliance

**C** For support call+1 800 522 6752

### 1892801-1

Rectangular Power Connectors, Connector Assembly, Plug, Board-to-Board, 18 Position, 6.35 mm / 2.54 mm [.1 in / .25 in] Centerline



#### For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-



# **Compatible Parts**



# Customers Also Bought

### 1892801-1

Rectangular Power Connectors, Connector Assembly, Plug, Board-to-Board, 18 Position, 6.35 mm / 2.54 mm [.1 in / .25 in] Centerline





# Documents

## **Product Drawings** MBXL VERT HDR 16S+2p

English

### **CAD** Files

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1892801-1\_2\_c-1892801-1-2.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1892801-1\_2\_c-1892801-1-2.3d\_igs.zip

English

**Customer View Model** 

## ENG\_CVM\_CVM\_1892801-1\_2\_c-1892801-1-2.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications Application Specification** 

English

**Product Environmental Compliance** MD\_1892801-1\_081820161026\_dmtec

English

MD\_1892801-1\_081820161026\_dmtec

English