# BACA-AMP-245 ACTIVE

#### **AMP SLIM**

TE Internal #: 1909783-1

Housing, Receptacle, Wire-to-Board, 2 Position, .047 in [1.2 mm] Centerline, Crimp, 1 Row, Black, Mating Retention, Wire & Cable,

AMP SLIM

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings











Connector Product Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 2

Centerline (Pitch): 1.2 mm [ .047 in ]

#### **Features**

#### **Product Type Features**

| Connector Product Type            | Housing       |
|-----------------------------------|---------------|
| Connector & Housing Type          | Receptacle    |
| Connector System                  | Wire-to-Board |
| Sealable                          | No            |
| Connector & Contact Terminates To | Wire & Cable  |
| Configuration Features            |               |
| Number of Positions               | 2             |
| Number of Rows                    | 1             |
| Electrical Characteristics        |               |
| Operating Voltage                 | 50 VAC        |
| Body Features                     |               |
| Primary Product Color             | Black         |



| Contact Layout                     | Inline                     |
|------------------------------------|----------------------------|
| Contact Type                       | Socket                     |
| Contact Current Rating (Max)       | 3 A                        |
| Termination Features               |                            |
| Termination Method to Wire & Cable | Crimp                      |
| Mechanical Attachment              |                            |
| Strain Relief                      | Without                    |
| Panel Mount Feature                | Without                    |
| PCB Mount Retention                | Without                    |
| Mating Retention Type              | Latch                      |
| Mating Retention                   | With                       |
| Connector Mounting Type            | Cable Mount (Free-Hanging) |
| Housing Features                   |                            |
| Housing Entry Configuration        | Both Ends Closed           |
| Housing Material                   | PA 66                      |
| Centerline (Pitch)                 | 1.2 mm[.047 in]            |
| Dimensions                         |                            |
| Connector Length                   | 3.46 mm[.136 in]           |
| Connector Height                   | 1.2 mm[.047 in]            |
| Connector Width                    | 3.5 mm[.138 in]            |
| Usage Conditions                   |                            |
| Operating Temperature Range        | -25 – 85 °C[-13 – 185 °F]  |
| Operation/Application              |                            |
| Circuit Application                | Power & Signal             |
| Industry Standards                 |                            |
| UL Flammability Rating             | UL 94V-0                   |
| Packaging Features                 |                            |
| Packaging Quantity                 | 1000                       |
| Packaging Method                   | Bag                        |

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>



| EU RoHS Directive 2011/65/EU                  | Compliant  |
|---|--|
| EU ELV Directive 2000/53/EC                   | Compliant  |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold  |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per<br>homogenous material. Also BFR/CFR/PVC<br>Free                                |
| Solder Process Capability                     | Not applicable for solder process capability   |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts



Also in the Series | AMP SLIM






PCB Headers & Receptacles(5)



Wire-to-Board Connector Assemblies & Housings(5)



# Customers Also Bought




TE Part #179227-4

AMP CT CRIMP-2 REC CONT AU



TE Part #20009605-08 FX293X-040B-0010-L



TE Part #2337019-1 UMCC Micro-Coax receptacle, Gen 1





TE Part #1-292134-0 CT BOX HDR ASSY V 10P AU W/KIN



TE Part #CONMHF1-SMD-G-T
U.FL/MHF1 Jack 50 Ohm PCB Surface
Mount



TE Part #CONMMCX002 MMCX Jack 50 Ohm PCB Through Hole







## **Documents**

### **Product Drawings**

WIRE TO BOARD HOUSING 1.2MM TOP ENTRY

English

## **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1909783-1\_C.2d\_dxf.zip

Housing, Receptacle, Wire-to-Board, 2 Position, .047 in [1.2 mm] Centerline, Crimp, 1 Row, Black, Mating Retention, Wire & Cable, AMP SLIM



English

**Customer View Model** 

ENG\_CVM\_CVM\_1909783-1\_C.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1909783-1\_C.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

**Application Specification** 

English