ENTRELEC | ENTRELEC SNK

TE Internal #: 1SNK710010R0000 Modular Terminal Blocks, Feed-Through, PI-Spring Terminal Block, Gray, Product Spacing .394 in [10 mm], 2 Position, DIN Rail, ENTRELEC SNK

View on TE.com >

Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: Feed-Through

Modular Terminal Block Product Type: PI-Spring Terminal Block

Primary Product Color: Gray

Product Spacing: 10 mm [.394 in]

Number of Positions: 2

Features

TE

Product Type Features

Modular Terminal Block Product Type	PI-Spring Terminal Block	
Configuration Features		
Gauge Type	A6 & 5.1 mm Dia.	
Number of Levels	1	
Number of Circuits	1	
Block Function	Feed-Through	
Number of Positions	2	
Electrical Characteristics		
Impulse Withstanding Voltage Rating (IEC)	8000 V	
Current Rating (CSA)	55 A	
Power Loss	1.8 W	
Short-Time Withstanding Current Rating @ 1s	1200 A	
Voltage Rating (IEC)	1000 V	
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	600 V	

Modular Terminal Blocks, Feed-Through, PI-Spring Terminal Block, Gray, Product Spacing .394 in [10 mm], 2 Position, DIN Rail, ENTRELEC SNK



Voltage Rating (CSA)	600 V	
Dielectric Withstanding Voltage (Max)	2200 V	
Current Rating (UL)	55 A	
Current Rating (IEC)	57 A	
Body Features		
Product Weight	27.2 g[1.071 oz]	
Primary Product Color	Gray	
Mechanical Attachment		
DIN Rail Mounting Type	TH35-15, TH35-7.5	
Connector Mounting Type	DIN Rail	
Housing Features		
Housing Material	Polyamide	
Dimensions		
Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp	.5 – 16 mm²	
Main Circuit Capacity - Twin Ferrule per Spring Clamp	.5 – 4 mm²	
Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp	.5 – 10 mm²	
Wire Stripping Length	15 mm[.591 in]	
Main Circuit Capacity - 1 Non-Insulated Ferrule per Spring Clamp	.5 – 10 mm²	
Main Circuit Capacity - 1 Insulated Ferrule per Spring Clamp	20 – 8 AWG	
Tool Size	4 mm[.157 in]	
Product Depth	47.5 mm	
Product Length	47.5 mm	
Product Height	82.5 mm	
Product Spacing	10 mm[.394 in]	
Usage Conditions		
Installation Temperature Range	-5 – 40 °C[23 – 104 °F]	
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]	
Industry Standards		
IP Rating	IP20	
UL Flammability Rating	UL 94V-0	

Modular Terminal Blocks, Feed-Through, PI-Spring Terminal Block, Gray, Product Spacing .394 in [10 mm], 2 Position, DIN Rail, ENTRELEC SNK



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




Modular Terminal Blocks, Feed-Through, PI-Spring Terminal Block, Gray, Product Spacing .394 in [10 mm], 2 Position, DIN Rail, ENTRELEC SNK





TE Part # 1SET112015R0000	TE Part # 1SNA164800R0300	TE Part # 1SNA168500R1200	TE Part # 1SNA168700R2200
WFD040-12-GR	PR3.G2	PR4	PR5

Also in the Series | ENTRELEC SNK



Customers Also Bought

& For support call+1 800 522 6752

Modular Terminal Blocks, Feed-Through, PI-Spring Terminal Block, Gray, Product Spacing .394 in [10 mm], 2 Position, DIN Rail, ENTRELEC SNK







TE Part #1SNK706410R0000 ZK2.5-SF



TE Part #1SNK900652R0000 SC-JB8-2

Documents

CAD Files

Customer View Model

ENG_CVM_CVM_1SNK710010R0000_B1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK710010R0000_B1.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_1SNK710010R0000_B1.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages ENTRELEC Terminal Block - Master Catalog

ENTRELEC Terminal Block - Master Catalog

English

Modular Terminal Blocks, Feed-Through, PI-Spring Terminal Block, Gray, Product Spacing .394 in [10 mm], 2 Position, DIN Rail, ENTRELEC SNK



ZK10

English

SNK SERIES TERMINAL BLOCKS

English

ENTRELEC Terminal Blocks Catalogue (RUS)

Essential Entrelec Terminal Blocks

French

Essential Entrelec Terminal Blocks

English

Essential Entrelec Terminal Blocks

Japanese

Product Environmental Compliance

Product Compliance Document

English

Product Compliance Document

English

Agency Approvals BV_MARINE_34077_B3

English