1SNK805740R0000 V ACTIVE



ENTRELEC | ENTRELEC SNK

TE Internal #: 1SNK805740R0000

Modular Terminal Blocks, Feed-Through, Female Plug, Gray, Product Spacing .204 in [5.2 mm], 2 Position, Push-in, Signal,

ENTRELEC SNK

View on TE.com >



Connectors > Terminal Blocks & Strips > Modular Terminal Blocks











Block Function: Feed-Through

Modular Terminal Block Product Type: Female Plug

Primary Product Color: Gray

Product Spacing: 5.2 mm [.204 in]

Number of Positions: 2

Features

Product Type Features

Modular Terminal Block Product Type	Female Plug
Configuration Features	
Gauge Type	A2 / 2.3 mm Dia.
Number of Levels	1
Number of Poles	2
Number of Circuits	1
Block Function	Feed-Through
Number of Positions	2
Electrical Characteristics	
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	600 V
Impulse Withstanding Voltage Rating (IEC)	6000 V
Voltage Rating (CSA)	600 V
Current Rating (CSA)	20 A
Dielectric Withstanding Voltage (Max)	2200 V



Short-Time Withstanding Current Rating @ 1s	300 A
Voltage Rating (IEC)	500 V
Current Rating (UL)	20 A
Current Rating (IEC)	24 A
Operating Voltage	500 VAC
Body Features	
Product Weight	5.37 g[.189 oz]
Primary Product Color	Gray
Termination Features	
Termination Method to Wire & Cable	Push-in
Mechanical Attachment	
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	Polyamide 6.6
Dimensions	
Main Circuit Capacity - 1 Rigid Stranded Conductor per Spring Clamp	.2 – 4 mm²
Wire Stripping Length	11 mm[.433 in]
Main Circuit Capacity - 1 Non-Insulated Ferrule per Spring Clamp	.22 – 2.5 mm²
Main Circuit Capacity - 1 Insulated Ferrule per Spring Clamp	26 – 14 AWG
Main Circuit Capacity - 1 Flexible Conductor per Spring Clamp	.22 – 2.5 mm²
Tool Size	3.5 mm[.138 in]
Product Depth	44.9 mm[1.75 in]
Product Width	5.2 mm[.204 in]
Product Length	44.9 mm[1.75 in]
Product Height	35.5 mm[1.38 in]
Product Spacing	5.2 mm[.204 in]
Wire Size	2.5 mm ²
Usage Conditions	
Installation Temperature Range	-5 - 40 °C[23 - 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]
Operation/Application	



Circuit Application	Signal
Industry Standards	
IP Rating	IP20
UL Flammability Rating	UL 94V-0

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts














TE Part # 1SET111027R0000 WF007-08-GR



TE Part # 1SET111029R0000 WF025-08-BL



TE Part # 1SNK140004R0000 MC512-YL



TE Part # 1SNK805010R0000 ZDK2.5-22



TE Part # 1SNK805014R0000 ZDK2.5-21



TE Part # 1SNK805015R0000 ZDK2.5-11



TE Part # 1SNK805017R0000 ZD2.5-22



TE Part # 1SNK805025R0000 ZDK2.5-11-BL



TE Part # 1SNK805150R0000 ZDK2.5-11-PE



TE Part # 1SNK805156R0000 ZD2.5-22-PE



TE Part # 1SNK805212R0000 ZDK2.5-D2-PE



TE Part # 1SNK805213R0000 ZDK2.5-D2



TE Part # 1SNK805214R0000 ZDK2.5-D1



TE Part # 1SNK805223R0000 ZDK2.5-D2-BL



TE Part # 1SNK805250R0000 ZDK2.5-D1-PE




Also in the Series | ENTRELEC SNK



Modular Terminal Blocks(320)



Terminal Block & Strip Conducting Accessories(67)



Terminal Block & Strip Insulating Accessories(31)

Customers Also Bought























Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SNK805740R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SNK805740R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK805740R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

ENTRELEC Terminal Block - Master Catalog

ENTRELEC Terminal Block - Master Catalog

English

Modular Terminal Blocks, Feed-Through, Female Plug, Gray, Product Spacing .204 in [5.2 mm], 2 Position, Push-in, Signal, ENTRELEC SNK



SNK SERIES TERMINAL BLOCKS

English

Essential Entrelec Terminal Blocks

French

Essential Entrelec Terminal Blocks

English

Essential Entrelec Terminal Blocks

Japanese

Agency Approvals

BV_MARINE_34077_B3

English