7012AH - ACTIVE

Agastat

TE Internal #: 2-1423157-0 Time Delay Relays, Knob, 120 – 110 VAC Input, 10A@240VAC A, On-Delay, 3 – 30 minutes Delay Time, Mounting Bracket View on TE.com >



Relays, Contactors & Switches > Relays > Time Delay Relays



Type of Control: Knob Time Delay Relay Input Voltage: 120 – 110 VAC Time Delay Relay Contact Current Rating: 10A@240VAC A Mode of Operation: On-Delay Delay Time: 3 – 30 minutes

Features

Product Type Features

Product Type	Relay
Relay Type	Time Delay
Product Category	Electromechanical Relays

Magnetic Blow-Out Device	Without
Configuration Features	
Multiple Timing Ranges	Without
Electrical Characteristics	
Actuating System	AC
Time Delay Relay Input Voltage	120 – 110 VAC
Contact Features	
Contact Arrangement	2 Form C, DPDT, 2 C/O
Type of Control	Knob
Time Delay Relay Contact Current Rating	10A@240VAC A
Delay Time	3 – 30 minutes
Termination Features	
Termination Type	Screw Terminals
Mechanical Attachment	

C For support call+1 800 522 6752

7012AH

Time Delay Relays, Knob, 120 – 110 VAC Input, 10A@240VAC A, On-Delay, 3 – 30 minutes Delay Time, Mounting Bracket



Time Delay Relay Mounting Type	Mounting Bracket
Dimensions	
Dimensions (L x W x H) (Approximate)	114.8 x 65.3 x 71.9 mm[4.523 x 2.572 x 2.832 in]
Usage Conditions	
Operating Temperature Range	-30 – 75 °C
Operation/Application	
Mode of Operation	On-Delay
Other	
Repeatability (Max)	±10%
Product Compliance For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)

Candidate List Declared Against: JUN 2020 (209) SVHC > Threshold: Cadmium oxide (10% in Contact) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free Not applicable for solder process capability

Halogen Content

Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

7012AH

Time Delay Relays, Knob, 120 – 110 VAC Input, 10A@240VAC A, On-Delay, 3 – 30 minutes Delay Time, Mounting Bracket



Compatible Parts



Customers Also Bought



TE Part #7-1393117-9 KUP-14A15-24=KU	TE Part #1-350777-9 02P UMNL V0 PLUG HSG BLACK	TE Part #9-1393104-0 KRPA-14DN-24=KRPA	TE Part #4-2027183-3 KUEP-11D15-125=RELAY,3A,2C, AGCDO,QC.187,



Documents

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_2-1423157-0_L.2d_dxf.zip

English

7012AH

Time Delay Relays, Knob, 120 – 110 VAC Input, 10A@240VAC A, On-Delay, 3 – 30 minutes Delay Time, Mounting Bracket



Customer View Model

ENG_CVM_CVM_2-1423157-0_L.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_2-1423157-0_L.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 5-1773450-5_sec12_7000

English