

Agastat

TE Internal #: 2-1423164-0 Time Delay Relays, Knob, 125 VDC Input, Timing Range (Off-Time) 1.5 – 15 seconds, 10A@240VAC A, Off-Delay, Mounting Bracket View on TE.com > **E** TE connectivity

Relays, Contactors & Switches > Relays > Time Delay Relays



Type of Control: Knob Time Delay Relay Input Voltage: 125 VDC Timing Range (Off-Time): 1.5 – 15 seconds Time Delay Relay Contact Current Rating: 10A@240VAC A Mode of Operation: Off-Delay

Features

Product Type Features

Product Type	Relay
Relay Type	Time Delay
Product Category	Electromechanical Relays

Magnetic Blow-Out Device	Without
Configuration Features	
Multiple Timing Ranges	Without
Electrical Characteristics	
Actuating System	DC
Time Delay Relay Input Voltage	125 VDC
Timing Range (Off-Time)	1.5 – 15 seconds
Contact Features	
Contact Arrangement	2 Form C, DPDT, 2 C/O
Type of Control	Knob
Time Delay Relay Contact Current Rating	10A@240VAC A
Termination Features	
Termination Type	Screw Terminals
Mechanical Attachment	

C For support call+1 800 522 6752

7022PC

Time Delay Relays, Knob, 125 VDC Input, Timing Range (Off-Time) 1.5 – 15 seconds, 10A@240VAC A, Off-Delay, Mounting Bracket



Time Delay Relay Mounting Type	Mounting Bracket
Dimensions	
Dimensions (L x W x H) (Approximate)	114.8 x 65.3 x 71.9 mm[4.523 x 2.572 x 2.83 in]
Usage Conditions	
Operating Temperature Range	-30 – 75 °C
Operation/Application	
Mode of Operation	Off-Delay
Other	
Repeatability (Max)	±5%
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)

Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Halogen Content

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

C For support call+1 800 522 6752

7022PC

Time Delay Relays, Knob, 125 VDC Input, Timing Range (Off-Time) 1.5 – 15 seconds, 10A@240VAC A, Off-Delay, Mounting Bracket





Customers Also Bought



KUEP-11D15-125=RELAY,3A,2C, AGCDO,QC.187,	7012PA=RLY,STD,ON,2P,125VDC,1									7	022AH	I=RLY,	STD,C)FF,2	P,12()VA(С,3	ŀ	KRP.	4-11	DG-'	125=	KRP	7	
		1	3				11 1																		
ETE	-	21	23 2	25	27 2	89	31 3	33		39 71															
TE Part #1SNA233041R2500 RC610 1->10 (X10) VERTICAL	TE Part #1SNA234030R2700 RC810 1->100 HORIZONTAL																								

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1423164-0_P.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1423164-0_P.3d_igs.zip

English

7022PC

Time Delay Relays, Knob, 125 VDC Input, Timing Range (Off-Time) 1.5 – 15 seconds, 10A@240VAC A, Off-Delay, Mounting Bracket



Customer View Model

ENG_CVM_CVM_2-1423164-0_P.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 5-1773450-5_sec12_7000

English