

#### CII | CII 3SBC Relay

TE Internal #: 2-1617072-2


1/5-Size Relays, 2 Form C, DPDT, 2 C/O, 26.5 VDC Input, 2 A, 26.5 VDC Coil Voltage, 1350  $\Omega$  Coil Resistance, 520 mW Coil Power

(DC), CII 3SBC Relay

View on TE.com >



Relays, Contactors & Switches > Relays > Mil-Aero Relays > 1/5-Size Relays > DPDT Signal Relay: Electrically-Held, 1/5-Size Relay



1/5-Size Relay Contact Arrangement: 2 Form C, DPDT, 2 C/O

1/5-Size Relay Input Voltage: 26.5 VDC

Coil Suppression Diode: Without

1/5-Size Relay Contact Current Rating: 2 A1/5-Size Relay Coil Voltage Rating: 26.5 VDC

All DPDT Signal Relay: Electrically-Held, 1/5-Size Relay (84)

#### **Features**

#### **Product Type Features**

Enclosure Type	Hermetically Sealed
Relay Type	Military/Aerospace High Performance
Coil Latching	Without
Product Type	Relay
MOSFET Driver	Without

#### **Configuration Features**

#### **Electrical Characteristics**

Actuating System	DC
Vibration	30G's, 10 – 3000Hz
Coil Magnetic System	Non-Polarized, Monostable
Shock	75G's, 6ms
Coil Power Measurement	Milliwatts
Coil Polarity Protection Diode	Without
1/5-Size Relay Input Voltage	26.5 VDC
Coil Suppression Diode	Without



1/5-Size Relay Coil Voltage Rating	26.5 VDC
1/5-Size Relay Coil Resistance	1350 Ω
1/5-Size Relay Coil Power Rating (DC)	520 mW
Contact Features	
1/5-Size Relay Contact Arrangement	2 Form C, DPDT, 2 C/O
1/5-Size Relay Contact Current Rating	2 A
Termination Features	
Termination Type	PC Pins
Mechanical Attachment	
1/5-Size Relay Mounting Type	Printed Circuit Board
Usage Conditions	

-65 – 125 °C

### **Product Compliance**

Operating Temperature Range

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not lead free process capable

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



## Compatible Parts



4PDT Signal Relay: Electrically-Held, 1

/5-Size Relay



# Also in the Series | CII 3SBC Relay




## Customers Also Bought















1/5-Size Relays, 2 Form C, DPDT, 2 C/O, 26.5 VDC Input, 2 A, 26.5 VDC Coil Voltage, 1350  $\Omega$  Coil Resistance, 520 mW Coil Power (DC), CII 3SBC Relay



TE Part #2-1617090-9 LS-8319 = LS RELAY

#### **Documents**

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2-1617072-2\_G\_c-2-1617072-2-g.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-1617072-2\_G\_c-2-1617072-2-g.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-1617072-2\_G\_c-2-1617072-2-g.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

5-1773450-5\_sec1\_3SBC

English

**RELAY** 

English