TE Internal #: 2-1718230-1

Housing for Male Terminals, Wire-to-Wire, 7 Position, .449 in [11.4 mm] Centerline, Sealable, Gray, Panel Mount, -40 – 248 °F [-40 – 120 °C], Key B

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > Circular DIN Housings











Connector System: Wire-to-Wire

Number of Positions: 7

Connector & Housing Type: Housing for Male Terminals

Centerline (Pitch): 11.4 mm [ .449 in ]

Sealable: Yes

All Circular DIN Housings (51)

## **Features**

### **Product Type Features**

Mixed & Hybrid Connector	No
Connector Shape	Circular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Male Terminals
Sealable	Yes
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	7
Electrical Characteristics	
Nominal Voltage Architecture	12 V, 24 V, 42 V, 48 V
Body Features	
Cable Exit Angle	180°
Primary Product Color	Gray



Connector & Keying Code	В
Contact Features	
Contact Size	1.5mm
Contact Type	Pin
Mating Pin Diameter	1.5 mm[.059 in]
Mechanical Attachment	
Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Panel Mount
Housing Features	
Housing Material	PBT GF
Centerline (Pitch)	11.4 mm[.449 in]
Dimensions	
Connector Height	28 mm[1.1 in]
Product Length	44 mm[1.73 in]
Usage Conditions	
Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C[158 °F][167 °F][176 ° F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F]
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Industry Standards	
Degree of Protection	IP69K
UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	450
Packaging Method	Вох
Other	
Carata I.I.	
Serviceable	Yes



## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts













TE Part # CAT-R7602-T273

ROUND CONNECTOR SYSTEM, PIN

AND SOCKET






# Customers Also Bought



TE Part #1-967622-5

JUN-POW-TIM GEH 12P



TE Part #967650-1 1.5MM BU-STE KPL 7P



TE Part #1718230-1 1,5MM PIN HSG 5-7 POS ASSY





TE Part #7-968971-1 AMP MCP 2.8 HSG 9 POS. 2.LOCKI



TE Part #965687-1 FIXING RING









### **Documents**

Product Drawings
1,5MM PIN HSG 5-7 POS ASSY

English

**CAD Files** 

3D PDF

3D

Customer View Model ENG\_CVM\_CVM\_2-1718230-1\_A.2d\_dxf.zip

Housing for Male Terminals, Wire-to-Wire, 7 Position, .449 in [11.4 mm] Centerline, Sealable, Gray, Panel Mount, -40 – 248 °F [-40 – 120 °C], Key B



English

**Customer View Model** 

ENG\_CVM\_CVM\_2-1718230-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-1718230-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

**Product Specification** 

English