# 2-794615-2 ACTIVE

### MATE-N-LOK | Micro MATE-N-LOK

TE Internal #: 2-794615-2

Rectangular Power Connectors, Housing, Plug, Wire-to-Panel / Wire-to-Wire, 22 Position, 3 mm [.118 in] Centerline, Wire & Cable,

Micro MATE-N-LOK

View on TE.com >




Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Housing

Connector & Housing Type: Plug

Connector System: Wire-to-Panel, Wire-to-Wire

Number of Positions: 22

Centerline (Pitch): 3 mm [.118 in]

#### **Features**

#### **Product Type Features**

Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Panel, Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	22
Number of Rows	2
Electrical Characteristics	
Operating Voltage	250 VDC
Contact Features	
Contact Retention Within Housing	Without

Pin

Contact Type



### **Termination Features**

Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Strain Relief	Without
Mating Alignment Type	Polarization
Mating Retention	With
Mating Alignment	With
Panel Mount Feature	With
Panel Mount Feature Type	Locking Latch
Mating Retention Type	Locking Tab
Connector Mounting Type	Panel Mount
Housing Features	
Centerline (Pitch)	3 mm[.118 in]
Housing Color	Black
Housing Material	Nylon
Dimensions	
Panel Thickness (Recommended)	1.57 – 2.3 mm[.062 – .091 in]
	1.57 – 2.3 mm[.062 – .091 in] 1.52 mm[.06 in]
Panel Thickness (Recommended)	
Panel Thickness (Recommended)  Compatible Insulation Diameter (Max)	1.52 mm[.06 in]
Panel Thickness (Recommended)  Compatible Insulation Diameter (Max)  Connector Height	1.52 mm[.06 in] 8.71 mm
Panel Thickness (Recommended)  Compatible Insulation Diameter (Max)  Connector Height  Product Length	1.52 mm[.06 in] 8.71 mm 33.85 mm
Panel Thickness (Recommended)  Compatible Insulation Diameter (Max)  Connector Height  Product Length  Row-to-Row Spacing	1.52 mm[.06 in] 8.71 mm 33.85 mm
Panel Thickness (Recommended)  Compatible Insulation Diameter (Max)  Connector Height  Product Length  Row-to-Row Spacing  Usage Conditions	1.52 mm[.06 in]  8.71 mm  33.85 mm  3 mm[.118 in]
Panel Thickness (Recommended)  Compatible Insulation Diameter (Max)  Connector Height  Product Length  Row-to-Row Spacing  Usage Conditions  Operating Temperature Range	1.52 mm[.06 in]  8.71 mm  33.85 mm  3 mm[.118 in]
Panel Thickness (Recommended)  Compatible Insulation Diameter (Max)  Connector Height  Product Length  Row-to-Row Spacing  Usage Conditions  Operating Temperature Range  Operation/Application	1.52 mm[.06 in]  8.71 mm  33.85 mm  3 mm[.118 in]  -40 – 105 °C[-40 – 221 °F]
Panel Thickness (Recommended)  Compatible Insulation Diameter (Max)  Connector Height  Product Length  Row-to-Row Spacing  Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application	1.52 mm[.06 in]  8.71 mm  33.85 mm  3 mm[.118 in]  -40 – 105 °C[-40 – 221 °F]
Panel Thickness (Recommended)  Compatible Insulation Diameter (Max)  Connector Height  Product Length  Row-to-Row Spacing  Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application  Industry Standards	1.52 mm[.06 in]  8.71 mm  33.85 mm  3 mm[.118 in]  -40 – 105 °C[-40 – 221 °F]  Power & Signal
Panel Thickness (Recommended)  Compatible Insulation Diameter (Max)  Connector Height  Product Length  Row-to-Row Spacing  Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application  Industry Standards  UL Flammability Rating	1.52 mm[.06 in]  8.71 mm  33.85 mm  3 mm[.118 in]  -40 – 105 °C[-40 – 221 °F]  Power & Signal  UL 94V-0
Panel Thickness (Recommended)  Compatible Insulation Diameter (Max)  Connector Height  Product Length  Row-to-Row Spacing  Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application  Industry Standards  UL Flammability Rating  Glow Wire Rating	1.52 mm[.06 in]  8.71 mm  33.85 mm  3 mm[.118 in]  -40 – 105 °C[-40 – 221 °F]  Power & Signal  UL 94V-0
Panel Thickness (Recommended)  Compatible Insulation Diameter (Max)  Connector Height  Product Length  Row-to-Row Spacing  Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application  Industry Standards  UL Flammability Rating  Glow Wire Rating  Packaging Features	1.52 mm[.06 in] 8.71 mm 33.85 mm 3 mm[.118 in]  -40 – 105 °C[-40 – 221 °F]  Power & Signal  UL 94V-0  Standard Part - Not Glow Wire



# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



Also in the Series | Micro MATE-N-LOK





Insertion & Extraction Tools(1)



Power Contacts(27)



Rectangular Power Connectors (466)

# Customers Also Bought



TE Part #2-794617-0 20POS,MICRO MNL,RCPT HSG



TE Part #794615-4
PANEL MT DBL ROW HSG 4 POS



TE Part #1-794617-6 16POS,MICRO MNL,RCPT HSG



TE Part #794617-8 8POS,MICRO MNL,RCPT HSG



TE Part #2-794617-4 24POS,MICRO MNL,RCPT HSG



TE Part #794615-6
PANEL MT DBL ROW HSG 6 POS



TE Part #1-794611-1 MICRO MNL RPT CNT,LS PC,15AU,L



TE Part #1-794612-1
PIN CONT 20-24 15 GOLD L/P



TE Part #1-794615-2
PANEL MT DBL ROW HSG 12 POS



## **Documents**

### **Product Drawings**

PANEL MT DBL ROW HSG 22 POS

English

## **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2-794615-2\_C1.2d\_dxf.zip



English

**Customer View Model** 

ENG\_CVM\_CVM\_2-794615-2\_C1.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-794615-2\_C1.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

SOFT\_SHELL\_PIN\_AND\_SOCKET\_CONNECTORS\_CATALOG

English

MICRO MATE-N-LOK CONNECTOR SYSTEM

English

### **Product Specifications**

**Application Specification** 

English

**Product Environmental Compliance** 

MD\_2-794615-2\_02242017334\_dmtec

English

MD\_2-794615-2\_02242017334\_dmtec

English