

MEAS | MEAS FX29

TE Internal #: 20009605-19 TE Internal Description: FX29K0-040B-0100-L Compact Compression Load Cell View on TE.com >



Sensors > Force Sensors > Force Sensor Elements > Compact Compression Load Cell



Force Sensor Element Sensor Type: **OEM Compression Load Cells**

Full Scale Range: 100 – 100 lbf

Operating Temperature Range: 0 – 50 °C [32 – 122 °F]

Output Signal: 14 Bit I2C

Zero Shift in CTR: ±.05 % of FS

All Compact Compression Load Cell (47)

Features

Product Type Features

Force Sensor Element Sensor Type

OEM Compression Load Cells

Electrical Characteristics

Supply Voltage	3 VDC
Full Scale Range	100 – 100 lbf
Signal Characteristics	
Output Signal	14 Bit I2C
Usage Conditions	
Operating Temperature Range	0-50 °C[32-122 °F]
Other	
Accuracy	±1 % of FS
Force Direction	Compression
Zero Shift in CTR	±.05 % of FS
Sensitivity Shift	±.05 % of FS

Product Compliance

For compliance documentation, visit the product page on TE.com>

FX29K0-040B-0100-L



EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Dodecamethylcyclohexasiloxane (D6) (.26% in component part) Decamethylcyclopentasiloxane (D5) (.12% in component part) Aticle Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts




Also in the Series | MEAS FX29

C For support call+1 800 522 6752



FX29K0-040B-0100-L





Customers Also Bought



Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_20009605-19_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_20009605-19_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_20009605-19_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages FX29 COMPRESSION LOAD CELL

English

FX29K0-040B-0100-L

FX29K0-040B-0100-L

