




Power Double Lock

TE Internal #: 2005247-1
Rectangular Power Connectors, Housing, Plug, Wire-to-Wire, 2
Position, 3.96 mm [.156 in] Centerline, Wire & Cable, UL 94V-0,
Power Double Lock

[View on TE.com >](#)

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors > Glow Wire Power Double Lock Plug



Rectangular Power Connector Type: **Housing**
Connector & Housing Type: **Plug**
Connector System: **Wire-to-Wire**
Number of Positions: **2**
Centerline (Pitch): **3.96 mm [.156 in]**

[All Glow Wire Power Double Lock Plug \(55\)](#)

Features

Product Type Features

Compatible With Discrete Wire Type	Stranded
Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	2
Number of Power Positions	0
Number of Signal Positions	0
Number of Rows	1

Electrical Characteristics

--	--



Operating Voltage	50 VAC, 300 VAC
-------------------	-----------------

Contact Features

Contact Layout	Inline
Contact Retention Within Housing	Without
Contact Type	Receptacle

Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------

Mechanical Attachment

Connector Mounting Type	Cable Mount (Free-Hanging)
-------------------------	----------------------------

Housing Features

Centerline (Pitch)	3.96 mm[.156 in]
Housing Color	Natural
Housing Material	PA 66

Usage Conditions

Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

Agency/Standard	CNR, USR
Approved Standards	CSA/C22.2 No. 182.3-M1987, UL 1977
UL Flammability Rating	UL 94V-0
Glow Wire Rating	GWT 750°C (Without Flame)

Packaging Features

Packaging Quantity	500
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	



Current ECHA Candidate List: JUNE 2023 (235)
Candidate List Declared Against: JUNE 2023 (235)
Does not contain REACH SVHC

Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 177898-1
POWER DBL LOCK PLUG HSG 2P




TE Part # 2005249-9
PDL 2P CAP 3.96 P/M(GWT) BLK




TE Part # 2005248-9
PDL 2P CAP 3.96 F/H (GWT) BLK


Also in the Series | Power Double Lock




Connector Contacts(1)



Insertion & Extraction Tools(2)



Power Contacts(23)



Rectangular Connector Locking(14)



Customers Also Bought

TE Part #177918-1
POWER DBL LOCK PLATE 2P

TE Part #917689-1
2.5 SIGNAL D/LOCK PLUG HSG 5P

TE Part #177914-1
AMP POWER DBL LOCK REC (S)

TE Part #177917-1
AMP POWER DBL LOCK TAB (L)

TE Part #179973-1
250 PL EX REC. 22-18AWG PTBR

TE Part #917701-1
2.5 SIGNAL DBL LOCK DLP 5P

TE Part #63677-1
312 FASTON REC 16-12 AWG TPBR

TE Part #1-368575-1
PDL 4P PLUG 3.96 D/R(GWT) NAT

TE Part #2-2005820-9
CLUSTER BLOCK 3P CLIP HSG(GWT)

TE Part #2108798-1
CLUSTER BLOCK 3P CLIP TPA HSG

Documents

Product Drawings
PDL 2P PLUG 3.96(GWT) NAT
English

CAD Files
3D PDF
3D
Customer View Model
ENG_CVM_CVM_2005247-1_B.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_2005247-1_B.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2005247-1_B.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Product Environmental Compliance

[MD_2005247-1_11012017340_dmtec](#)

English

[MD_2005247-1_11012017340_dmtec](#)

English