# 2008563-1 ✓ ACTIVE

#### Buchanan WireMate

TE Internal #: 2008563-1

Poke-In Connectors, Wire-to-Board, 1 Position, Wire & Cable, Height .154 in [3.9 mm], Surface Mount, 18 – 22 AWG Wire Size,

Power & Signal

View on TE.com >



#### Connectors > Lighting Connectors > Poke-In Connectors











Connector System: Wire-to-Board

Number of Positions: 1

Connector & Contact Terminates To: Wire & Cable

Connector Height: 3.9 mm [.154 in]

Termination Method to Printed Circuit Board: Surface Mount

PCB Contact Termination Area Plating Material Thickness

# **Features**

### **Product Type Features**

Contact Fabrication

| Product Line                      | Poke-In       |
|-----------------------------------|---------------|
| Connector System                  | Wire-to-Board |
| Connector & Contact Terminates To | Wire & Cable  |
| Configuration Features            |               |
| Number of Positions               | 1             |
| Electrical Characteristics        |               |
| Operating Voltage                 | 250 VAC       |
| Body Features                     |               |
| Header Mating Direction           | Horizontal    |
| Primary Product Color             | White         |
| Contact Features                  |               |

Stamped & Formed

3 μm[118.11 μin]



| Contact Layout                                       | Inline   |
|--|--|
| Contact Mating Area Plating Material Thickness       | 3 μm[118 μin]                                    |
| Contact Mating Area Plating Material                 | Tin  |
| PCB Contact Termination Area Plating Material Finish | Matte  |
| Contact Mating Area Plating Material Finish          | Matte  |
| Contact Underplating Material                        | Nickel   |
| PCB Contact Termination Area Plating Material        | Tin  |
| Contact Current Rating (Max)                         | 4 A  |
| Termination Features                                 |  |
| Termination Method to Printed Circuit Board          | Surface Mount                                    |
| Mechanical Attachment                                |  |
| PCB Mount Retention                                  | With   |
| Connector Mounting Type                              | Board Mount                                      |
| Dimensions   |  |
| Compatible Insulation Diameter Range                 | 2.1 mm[.083 in]                                  |
| Connector Height                                     | 3.9 mm[.154 in]                                  |
| Wire Size  | 18 – 22 AWG                                      |
| Usage Conditions                                     |  |
| Operating Temperature Range                          | -40 - 105 °C[-40 - 221 °F]                       |
| Operation/Application                                |  |
| Circuit Application                                  | Power & Signal                                   |
| Industry Standards                                   |  |
| Agency/Standard                                      | CSA, UL  |
| Approved Standards                                   | CSA/C22.2 No. 182.3-M1987, UL 1977, UL<br>E28476 |
| UL Flammability Rating                               | UL 94V-0   |
| Packaging Features                                   |  |
| Packaging Method                                     | SMT Pocket Tape                                  |
|  |  |

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|------------------------------|-----------|
|------------------------------|-----------|



| EU ELV Directive 2000/53/EC                   | Compliant   |
|---|---|
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                       |
| Solder Process Capability                     | Reflow solder capable to 260°C  |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



# **Customers Also Bought**







TE Part #1470364-4

1.0MM W T B RECPT,4POS HOUSING

















### **Documents**

### **Product Drawings**

Connector, 1 Pos SMT Poke-In

English

### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_2008563-1\_A.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2008563-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2008563-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

SMT\_AND\_THRU-HOLE\_POKE-IN\_WIRE\_LIGHTING\_CONNECTORS

English

## **Product Specifications**

**Application Specification** 

English

### **Product Environmental Compliance**

Product Compliance Document

Poke-In Connectors, Wire-to-Board, 1 Position, Wire & Cable, Height .154 in [3.9 mm], Surface Mount, 18 – 22 AWG Wire Size, Power & Signal



English

Product Compliance Document

English

Agency Approvals

**UL Report** 

English