2041126-1 ACTIVE

TE Internal #: 2041126-1 RJ45 Connectors, RJ45, Single Port, 1 x 1, RJ Type Jacks & Plugs, Standard Connector Contact Density, Jack, Shielded, Cat 3, Standard - Latch Down

View on TE.com >

Connectors > Modular Jacks & Plugs > RJ45 Connectors



Modular Jack & Plug Interface Type: RJ45 Port Configuration: Single Port Port Matrix Configuration: 1 x 1 Modular Jacks & Plugs Products: RJ Type Jacks & Plugs Connector Contact Density: Standard

Features

Product Type Features



Connector Product Type	Connector Assembly				
Modular Jack & Plug Interface Type	RJ45				
Modular Jacks & Plugs Products	RJ Type Jacks & Plugs				
Modular Connector Style	Jack				
Grounding Options	PCB Ground				
Connector & Contact Terminates To	Printed Circuit Board				
Configuration Features					
Status Indicator Type	None				
Number of PCB Ground Tabs	2				
Port Configuration	Single Port				
Port Matrix Configuration	1 x 1				
Connector Contact Density	Standard				
Number of Positions	8				
Number of Loaded Positions	8				
PCB Mount Orientation	Right Angle				

RJ45 Connectors, RJ45, Single Port, 1 x 1, RJ Type Jacks & Plugs, Standard Connector Contact Density, Jack, Shielded, Cat 3, Standard - Latch Down



Body Features

Shield Plating Material	Nickel							
Shield Material	Brass							
Modular Jack Latch Orientation	Standard - Latch Down							
Connector Profile	Offset - Overhangs PCB							
Contact Features								
Contact Underplating Material	Nickel							
PCB Contact Termination Area Plating Material	Gold Flash							
Contact Current Rating (Max)	1 A							
Contact Mating Area Plating Material	Gold							
Contact Base Material	Phosphor Bronze							
Contact Mating Area Plating Material Thickness	.15 μm[6 μin]							
Termination Features								
Termination Method to Printed Circuit Board	Surface Mount							
Mechanical Attachment								
Panel Mount Feature	Without							
Connector Mounting Type	Board Mount							

Housing Features

Mating Entry Location	Side						
Centerline (Pitch)	1.02 mm[.04 in]						
Housing Color	Black						
Housing Material	High Temperature Thermoplastic						
Dimensions							
PCB Thickness (Recommended)	1.2 mm						
Connector Height	11.45 mm[.45 in]						
Usage Conditions							
Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]						
Operation/Application							
Shielded	Yes						
Circuit Application	Signal						
Industry Standards							

C For support call+1 800 522 6752

RJ45 Connectors, RJ45, Single Port, 1 x 1, RJ Type Jacks & Plugs, Standard Connector Contact Density, Jack, Shielded, Cat 3, Standard - Latch Down



UL Flammability Rating	UL 94V-0			
Performance Category	Cat 3			
Packaging Features				
Packaging Quantity	230			
Packaging Method	Tape & Reel			

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant			
EU ELV Directive 2000/53/EC	Compliant			
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold			
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC			
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.			
Solder Process Capability	Reflow solder capable to 260°C			

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

RJ45 Connectors, RJ45, Single Port, 1 x 1, RJ Type Jacks & Plugs, Standard Connector Contact Density, Jack, Shielded, Cat 3, Standard - Latch Down





Customers Also Bought



5 MTE HDR SRRA LATCH W/HLDWN	07 MTE HDR SRRA LATCH W/HLDWN	4X4 MTE SHRD PIN SR LATCH .100	4X5 MTE RCPT SR LATCH .100CL



Documents

Product Drawings MODULAR JACK, RJ45, SMT TYPE,AU:6u''

English

CAD Files

Customer View Model

ENG_CVM_CVM_2041126-1_A3.3d_igs.zip

English

Customer View Model

RJ45 Connectors, RJ45, Single Port, 1 x 1, RJ Type Jacks & Plugs, Standard Connector Contact Density, Jack, Shielded, Cat 3, Standard - Latch Down



ENG_CVM_CVM_2041126-1_A3.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_2041126-1_A3.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications
Product Specification

English