



Connectors > Connector Accessories > Connector Backshells



Connector Backshell Product Type: **Backshell**

Primary Product Material: **Nylon 6/6**

Number of Positions: **4**

Sealable: **No**

Operating Temperature Range: **-40 – 120 °C [ -40 – 248 °F ]**

Features

Product Type Features

Connector Backshell Product Type	Backshell
Sealable	No

Configuration Features

Number of Positions	4
---------------------	---

Body Features

Cable Exit Angle	180°
Primary Product Color	Black
Primary Product Material	Nylon 6/6

Usage Conditions

Operating Temperature (Max)	120 °C[248 °F]
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 2345394-1  
4POS,AMP MCP 2.8,REC HSG ASSY,  
SLD,COD 1




TE Part # 2345394-2  
4POS,AMP MCP 2.8,REC HSG ASSY,  
SLD,COD 2


Also in the Series | Superseal Pro



Automotive Housings(87)




Connector Backshells(15)




Other Automotive Connector Accessories(1)




Customers Also Bought




TE Part #1452997-1  
76 POS 2-NDRAY LOCK BIG




TE Part #936421-2  
HYBRID 42P PLUG ASSY BLK




TE Part #1241608-6  
MQS1,5 Ag rec CB unseal. 0,75-1,5




TE Part #1452503-3  
MCON 1.2 CB REC SRC AG




TE Part #2050832-2  
COVER FOR 3P SENSOR CONNECTOR




TE Part #936111-1  
2.8mm Sealed 2P Cover




TE Part #2050992-1  
SEALED JPT HOUSING ASSEMBLY, 10P



TE Part #1-1452424-2  
BLIND PLUG FOR MCON 1.2 CB (1. 10P



TE Part #2050049-1  
3POS 2.8MM SENSOR PLUG ASSY



TE Part #2050046-4  
2POS 2.8MM SENSOR PLUG ASSY.

Documents

Product Drawings

COVER FOR 4P SENSOR CONNECTOR

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_2050780-2\_E.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_2050780-2\_E.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_2050780-2\_E.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.



Product Specifications

Product Specification

English