

### CHAMP | CHAMP Docking Connectors

TE Internal #: 2129260-2

Docking Connectors, Receptacle, Cable-to-Board, 40 Position, .6 mm [.024 in] Centerline, 3 Row, 40 Signal Positions, CHAMP

**Docking Connectors** 

View on TE.com >



Connectors > Dock Connectors & Guide Hardware > Docking Connectors











Docking Connector Style: Receptacle

Connector System: Cable-to-Board

Number of Positions: 40

Centerline (Pitch): .6 mm [ .024 in ]

Number of Rows: 3

#### **Features**

### **Product Type Features**

Docking Connector Style	Receptacle
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	40
Number of Rows	3
Number of Signal Positions	40
Number of Power Positions	O
PCB Mount Orientation	Right Angle
Body Features	
Shell Base Material	Stainless Steel
Contact Features	

.38 µm

Contact Mating Area Plating Material Thickness



Contact Mating Area Plating Material	Gold
Contact Base Material	Copper Alloy
Number of Utility Contacts	0
Contact Current Rating (Max)	.5 A, 1 A
Termination Features	
Termination Post & Tail Length	1.5 mm[.06 in]
Termination Method to Printed Circuit Board	Surface Mount, Through Hole - Solder
Mechanical Attachment	
PCB Mount Alignment	With
PCB Mount Retention Type	Hold-Down Post
PCB Mount Retention	With
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Thermoplastic
Housing Color	Black
Centerline (Pitch)	.6 mm[.024 in]
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	

# Operation/Application

Circuit Application	Power & Signal

## **Industry Standards**

## Packaging Features

Packaging Quantity	600
Packaging Method	Reel

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold



EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JUNE 2023 (235)

Candidate List Declared Against: JUNE 2023 (235)

Does not contain REACH SVHC

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per

Free

Solder Process Capability Reflow solder capable to 260°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts









homogenous material. Also BFR/CFR/PVC



Also in the Series | CHAMP Docking Connectors





Connector Caps & Covers(28)



D-Sub Locking & Mounting(29)



Docking Connector Guide Hardware(5)



Docking Connectors(31)



IDC D-Sub Connectors(77)



Customers Also Bought




TE Part #1-917337-2 DYNAMIC D-3 VERTI. HDR ASSY 2P



TE Part #1717468-3 SEMI-HARD TRAY DDR SODIMM SOCKET 200P 6



TE Part #1-770966-0 02P MINI UMNL R/A HDR ASSY SN











## **Documents**

**Product Drawings** 

REC ASSY 0.6mm CHAMP DOCKING C

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2129260-2\_B\_c-2129260-2-b.2d\_dxf.zip

Docking Connectors, Receptacle, Cable-to-Board, 40 Position, .6 mm [.024 in] Centerline, 3 Row, 40 Signal Positions, CHAMP Docking Connectors



English

**Customer View Model** 

ENG\_CVM\_CVM\_2129260-2\_B\_c-2129260-2-b.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2129260-2\_B\_c-2129260-2-b.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of usi

## Datasheets & Catalog Pages

6-1773457-9\_CHAMP\_DOCKING\_CONNECTOR\_QUICK\_REFERENCE\_GUIDE

English

**Product Specifications** 

**Product Specification** 

English