Nano MQS

TE Internal #: 2141404-1

Housing for Female Terminals, Wire-to-Board / Wire-to-Device / Wire-to-Wire, 20 Position, .07 in [1.8 mm] Centerline, Black, Wire &

Cable, Nano MQS

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > MQS, CONNECTOR HOUSING











Connector System: Wire-to-Board, Wire-to-Device, Wire-to-Wire

Number of Positions: 20

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 1.8 mm [.07 in]

Sealable: No

All MQS, CONNECTOR HOUSING (573)

Features

Product Type Features

rioduct Type reatures	
Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Board, Wire-to-Device, Wire-to- Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	20
Number of Rows	2
Electrical Characteristics	

12 VDC

Operating Voltage



Nominal Voltage Architecture	12 V
Body Features	
Cable Exit Angle	180°
Primary Product Color	Black
Connector & Keying Code	A
Contact Features	
Contact Size	.5mm
Contact Type	Receptacle
Mating Tab Width	.5 mm[.019 in]
Contact Current Rating (Max)	3 A
Mechanical Attachment	
Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PBT GF
Centerline (Pitch)	1.8 mm[.07 in]
Dimensions	
Connector Height	7.2 mm[.283 in]
Product Width	16.45 mm[.648 in]
Product Length	24.18 mm[.952 in]
Row-to-Row Spacing	5.9 mm[.232 in]
Usage Conditions	
Operating Temperature (Max)	120 °C[248 °F]
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Operation/Application	
Conforms to KOMAX Automatic Component Insertion Guideline	Per Version 5 with Increased Setup Effort /Limited Process Speed
Circuit Application	Signal
Industry Standards	



UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	3000
Packaging Method	Box & Carton
Other	
Serviceable	No
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # 2208165-1 20POS,NANO MQS,HEADER ASSY, CODA



MQS, RECEPTACLE AND TAB

TE Part # 8-2177729-9 20POS,TAB 0.5X0.4,HEADER ASSY



TE Part # 1-2208166-2 20POS,NANO MQS,HEADER HSG, CODB

Also in the Series | Nano MQS




Automotive Housings(60)



Automotive Terminals/9




Insertion & Extraction Tools(6)




PCB Headers & Receptacles(28)

Customers Also Bought




TE Part #1-1355350-1 MQS ABDECKKAPPE 18P



TE Part #041925-000 202A121-4/86-0



TE Part #53420-1 TERMINAL,PIDG PVF2 R 16-14



TE Part #1939608-3 0.64/2.3 SERIES 20POS.CAP HOUSING ASSY



TE Part #1939608-4 0.64/2.3 SERIES 20POS.CAP HOUSING ASSY



TE Part #3-2209521-1 REC CONN CVR ASSY,46POS,MCON 12,90 DEG



TE Part #5-1719105-1 14POS,JPT,REC.HSG,BK



TE Part #ASHD624-44420PN025 PLUG ASSY.ASHD. 44420 PLANFORM.



TE Part #2236917-1 SENSOR CPL, P441,ASSY

Documents

Product Drawings

20POS,NANOMQS,REC HSG,CODE A

English

20POS, NANOMQS, REC HSG, CODE A

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2141404-1_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2141404-1_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2141404-1_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Micro Quadlok Interconnection System (MQS)

English

Product Specifications

Application Specification

English

Application Specification

English