
2170614-1 - ACTIVE

TE Internal #: 2170614-1 SFP, SFP+ & zSFP+, Cage Assembly, Data Rate (Max) 4 Gb/s, Internal/External EMI Springs, SFP+, With Lightpipe, 1 x 1, Dual Round, Standard, Standard

View on TE.com >



Connectors > Pluggable IO Connectors & Cages > SFP, SFP+ & zSFP+



Pluggable I/O Product Type: Cage Assembly

Data Rate (Max): 4 Gb/s

EMI Containment Feature Type: Internal/External EMI Springs

Pluggable I/O Applications: SFP+

Lightpipe Options: With Lightpipe

Features

Product Type Features

Form Factor	SFP
Cage Type	Single
Pluggable I/O Product Type	Cage Assembly
Lightpipe Options	With Lightpipe

Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Port Matrix Configuration	1 x 1
Lightpipe Configuration	Dual Round
Lightpipe Style	Standard
Lightpipe Profile	Standard
Number of Ports	1
Electrical Characteristics	
Data Rate (Max)	4 Gb/s
Termination Features	
Termination Post & Tail Length	3 mm[.118 in]
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Mechanical Attachment	

2170614-1

SFP, SFP+ & zSFP+, Cage Assembly, Data Rate (Max) 4 Gb/s, Internal/External EMI Springs, SFP+, With Lightpipe, 1 x 1, Dual Round, Standard, Standard



Connector Mounting Type	Board Mount
Housing Features	
Cage Material	Copper Alloy
Dimensions	
PCB Thickness (Recommended)	1.5 mm[.059 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Heat Sink Compatible	No
For Use With Pluggable I/O Products	SFP SMT Connector
Pluggable I/O Applications	SFP+
Circuit Application	Signal
Packaging Features	
Packaging Method	Tray
Other	

EMI Containment Feature Type

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent

2170614-1

SFP, SFP+ & zSFP+, Cage Assembly, Data Rate (Max) 4 Gb/s, Internal/External EMI Springs, SFP+, With Lightpipe, 1 x 1, Dual Round, Standard, Standard



chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



Customers Also Bought



 TE Part #87456-6
 TE Part #5222132-1
 TE Part #1934229-1
 TE Part #1761008-3

 10 MODIV HSG DR MRKD .100CL
 JACK,VERTICAL,PCB,75 OHM,BNC
 Tin Man Recpt Assy 3 Pair16 Column
 SFP 1X4 CAGE & LIGHT PIPE KIT





Documents

C For support call+1 800 522 6752

TE Part #2170288-1

QSFP

1X4 CAGE ASSEMBLY, THRU BEZEL,

2170614-1

SFP, SFP+ & zSFP+, Cage Assembly, Data Rate (Max) 4 Gb/s, Internal/External EMI Springs, SFP+, With Lightpipe, 1 x 1, Dual Round, Standard, Standard



Product Drawings cage assy, 20 press fit, sfp w **CAD** Files **Customer View Model** ENG_CVM_CVM_2170614-1_A.2d_dxf.zip **Customer View Model** ENG_CVM_CVM_2170614-1_A.3d_igs.zip **Customer View Model** ENG_CVM_CVM_2170614-1_A.3d_stp.zip By downloading the CAD file I accept and agree to the Terms and Conditions of use

Product Specifications

Application Specification

English

English

3D PDF

English

English

English

3D

Product Environmental Compliance TE Material Declaration

English