# 

### CGS | CGS 3430

TE Internal #: 2176567-6 20K Ω, Thick Film, Power Resistor, 1 %, 2 Termination, 1225, Taped & Reeled, 3 W, ±100 ppm/°C, Solder, 3.2 x 6.4 x .65 mm, CGS 3430 View on TE.com >



Passive Components > Resistors > Surface Mount Resistors



Resistor Type: Power Resistor

Number of Terminations: 2

Package Size Code: 1225

Packaging Method: Taped & Reeled

Passive Component Tolerance: 1%

### Features

## Product Type Features

| Product Type                | Fixed Resistor        |
|-----------------------------|-----------------------|
| Resistor Type               | Power Resistor        |
| Package Size Code           | 1225                  |
| Element Type                | Thick Film            |
| Configuration Features      |                       |
| Number of Resistors         | 1                     |
| Electrical Characteristics  |                       |
| Voltage Rating              | 200 V                 |
| Passive Component Tolerance | 1 %                   |
| Resistance Class            | $1k\Omega - 1M\Omega$ |
| Resistance Value            | 20ΚΩ                  |
| Power Rating                | 3 W                   |
| Termination Features        |                       |
| Number of Terminations      | 2                     |

### 3430A3F20KTDF

20K Ω, Thick Film, Power Resistor, 1 %, 2 Termination, 1225, Taped & Reeled, 3 W, ±100 ppm/°C, Solder, 3.2 x 6.4 x .65 mm, CGS 3430



| Surface Mount Resistor Termination Type   | Solder   |
|---|--|
| Dimensions  |  |
| Passive Component Dimensions  | 3.2 x 6.4 x .65 mm   |
| Usage Conditions  |  |
| Operating Temperature Range   | -55 – 155 °C   |
| Temperature Coefficient   | ±100 ppm/°C  |
| Packaging Features  |  |
| Packaging Method  | Taped & Reeled   |
|   |  |
| For compliance documentation, visit the product page on TE.com>   | Compliant with Exemptions  |
| For compliance documentation, visit the product page on TE.com><br>EU RoHS Directive 2011/65/EU   | Compliant with Exemptions  |
| Product Compliance<br>For compliance documentation, visit the product page on TE.com><br>EU RoHS Directive 2011/65/EU<br>EU ELV Directive 2000/53/EC<br>China RoHS 2 Directive MIIT Order No 32, 2016 | Compliant with Exemptions<br>Not Compliant<br>Restricted Materials Above Threshold |

### Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Reflow solder capable to 260°C

### Solder Process Capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**

### 3430A3F20KTDF

20K Ω, Thick Film, Power Resistor, 1 %, 2 Termination, 1225, Taped & Reeled, 3 W, ±100 ppm/°C, Solder, 3.2 x 6.4 x .65 mm, CGS 3430





# Also in the Series | CGS 3430



## Documents

Product Drawings 3430 A3 1% 20K 100ppm 1k RL English

### **CAD** Files

**Customer View Model** 

### ENG\_CVM\_CVM\_2176567-6\_BA.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_2176567-6\_BA.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2176567-6\_BA.2d\_dxf.zip

English

### 3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

Datasheet - CGS 3430 Series

English

Automotive Grade Wide Terminal Chip Resistor - Type 3430 Series

English

**Product Environmental Compliance** 

**S** For support call+1 800 522 6752

### 3430A3F20KTDF

20K Ω, Thick Film, Power Resistor, 1 %, 2 Termination, 1225, Taped & Reeled, 3 W, ±100 ppm/°C, Solder, 3.2 x 6.4 x .65 mm, CGS 3430



Product Compliance Document

English

Product Compliance Document

English