2199119-5 ACTIVE

M.2 NGFF

TE Internal #: 2199119-5

M.2 Connectors, Height .126 in [3.2 mm], Connector & Keying Code B, Gold, Power, -40 – 185 °F [-40 – 85 °C], M.2 NGFF


View on TE.com >



Connectors > PCB Connectors > Card Edge Connectors > M.2 Connectors > M.2 Connectors











Connector Height: 3.2 mm [.126 in]

Connector & Keying Code: B

Contact Mating Area Plating Material: Gold

Connector System: Board-to-Board

Number of Positions: 67

All M.2 Connectors (29)

Features

Product Type Features

Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Rows	2
PCB Mount Orientation	Right Angle
Number of Positions	67
Electrical Characteristics	
Operating Voltage	50 VAC
Body Features	
Primary Product Color	Black
Connector & Keying Code	В

30 µin

Contact Features



PCB Contact Termination Area Plating Material Finish	Matte
PCB Contact Termination Area Plating Material	Gold Flash, Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold
Contact Current Rating (Max)	.5 A
Termination Features	
Termination Method to Printed Circuit Board	Surface Mount
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	High Temperature Thermoplastic
Treatering material	riigii remperatare memopiastic
Centerline (Pitch)	.5 mm[.02 in]
Centerline (Pitch)	
Centerline (Pitch) Dimensions	.5 mm[.02 in]
Centerline (Pitch) Dimensions Connector Length	.5 mm[.02 in] 21.9 mm[.862 in]
Centerline (Pitch) Dimensions Connector Length Connector Width	.5 mm[.02 in] 21.9 mm[.862 in] 8.7 mm[.343 in]
Centerline (Pitch) Dimensions Connector Length Connector Width Connector Height	.5 mm[.02 in] 21.9 mm[.862 in] 8.7 mm[.343 in]
Centerline (Pitch) Dimensions Connector Length Connector Width Connector Height Usage Conditions	.5 mm[.02 in] 21.9 mm[.862 in] 8.7 mm[.343 in] 3.2 mm[.126 in]
Centerline (Pitch) Dimensions Connector Length Connector Width Connector Height Usage Conditions Operating Temperature Range	.5 mm[.02 in] 21.9 mm[.862 in] 8.7 mm[.343 in] 3.2 mm[.126 in]

Product Compliance

Packaging Features

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC

Tape & Reel



Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC
	Free

Reflow solder capable to 245°C

Product Compliance Disclaimer


Solder Process Capability

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series M.2 NGFF



Customers Also Bought







TE Part #1SNA103354R0200 PPF2

TE Part #1SNA103940R0200 AF50 COLISE PAR 2000 PIECES

TE Part #1SNA103946R2400 ENF5 COLISE PAR 2000

TE Part #1SNA103947R2500 ENF7 COLISE PAR 2000

TE Part #1SNA103949R0700 ENF25 COLISE PAR 2000

Documents

Product Drawings

M.2 0.5PITCH 3.2H KEY B 30U" AU

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2199119-5_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2199119-5_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2199119-5_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

1-1773702-1_NGFF_QRG-EN

English

1-1773706-1NGFF_QRG-SC

Product Specifications

Application Specification

English

Product Environmental Compliance

M.2 Connectors, Height .126 in [3.2 mm], Connector & Keying Code B, Gold, Power, -40 – 185 °F [-40 – 85 °C], M.2 NGFF



Product Compliance Document

English

Product Compliance Document

English