

LUMAWISE

TE Internal #: 2213614-3

PCB Mount Hermaphroditic Connector, Horizontal, Board-to-Board, 6 Position, 4 mm Centerline, Gold, Surface Mount, Power,

Natural

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles











PCB Connector Assembly Type: PCB Mount Hermaphroditic Connector

PCB Mount Orientation: Horizontal
Connector System: Board-to-Board

Number of Positions: 6
Centerline (Pitch): 4 mm

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Hermaphroditic Connector
Connector System	Board-to-Board
Sealable	No

Configuration Features

PCB Mount Orientation	Horizontal
Number of Positions	6
Board-to-Board Configuration	Co-Planar

Body Features

Primary Product Color	Natural
Contact Features	

Mating Tab Width	3.05 mm[.12 in]
Mating Tab Thickness	.4 mm[.016 in]
Contact Mating Area Plating Material Finish	Matte
Contact Underplating Material	Nickel



Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	1.52 – 3.04 μm
Contact Type	Hermaphroditic
Contact Current Rating (Max)	6 A
Termination Features	
Rectangular Termination Post & Tail Thickness	.4 mm[.016 in]
Rectangular Termination Post & Tail Width	1 mm[.04 in]
Termination Method to Printed Circuit Board	Surface Mount
Mechanical Attachment	
Mating Alignment	Without
PCB Mount Retention	Without
PCB Mount Alignment	Without
Connector Mounting Type	Board Mount
Housing Features	
Centerline (Pitch)	4 mm
Housing Material	LCP
Usage Conditions	
Operating Temperature Range	-40 – 105 °C
Operation/Application	
Circuit Application	Power
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Type	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235)



Candidate List Declared Against: JUL 2021 (219)

Does not contain REACH SVHC

Low Halogen - Br. Cl. F. L < 900 ppm per

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

Free

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought





















Documents

Product Drawings

HERM BLADE & REC,6 POS, LATCH, SEL GOLD

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2213614-3_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2213614-3_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2213614-3_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Hermaphroditic Connectors with Select Gold Plating Flyer

Hermaphroditic Connectors with Select Gold Plating Flyer

English

Product Specifications

Application Specification

English

Agency Approvals

PCB Mount Hermaphroditic Connector, Horizontal, Board-to-Board, 6 Position, 4 mm Centerline, Gold, Surface Mount, Power, Natural



UL Report

English