

CoolSplice | CoolSplice Connectors

TE Internal #: 2213800-3

Splices, Butt Splice, 22 – 20 AWG Wire Size, .34 – .52 mm² Wire Size, Splice Capacity 4, End Feed, Phosphor Bronze, CoolSplice

Connectors

View on TE.com >



Terminals & Splices > Splices > CoolSplice Quick Connect Splice











Wire Size: .34 – .52 mm²

Sealable: No

Splice Capacity: 4

Splice Features: End Feed

All CoolSplice Quick Connect Splice (12)

Features

Product Type Features

Sealable	No
Splice Type	Butt Splice
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Insulation Support
Configuration Features	
Splice Capacity	4
Compatible With Wire & Cable Type	Discrete Wire
Electrical Characteristics	
Current Rating	5 A
Operating Voltage	600 V
Body Features	
Button Color	Green

End Feed

Splice Features



Contact Features

Contact Base Material	Phosphor Bronze
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Wire Size	.34 – .52 mm²
Compatible Insulation Diameter Range	2.85 mm[.112 in]
Product Length	36.4 mm[1.433 in]
Usage Conditions	
Insulation Option	Fully Insulated
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Agency/Standard	IEC, UL
Approved Standards	IEC 60988-2-3, UL 1977, UL 2459
UL Flammability Rating	UL 94V-2
Government Qualified Splice	No
Packaging Features	
Packaging Method	Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free



Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | CoolSplice Connectors



Customers Also Bought

















TE Part #254320-E STVC/3 30 F ABC VVV 7-00 TL 4,0 * 247 E0

Documents

Product Drawings

COOLSPLICE NEW STANDARD

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2213800-3_D2.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2213800-3_D2.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2213800-3_D2.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

CoolSplice New Standard flyer (Chinese)

English

CoolSplice Connector

CoolSplice Connector

English

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

DEKRA_CB_NL-68996_C1 CoolSplice IEC60998-2-3

English

Splices, Butt Splice, 22 – 20 AWG Wire Size, .34 – .52 mm² Wire Size, Splice Capacity 4, End Feed, Phosphor Bronze, CoolSplice Connectors

