

### RAST | RAST 5 IDC Connectors

TE Internal #: 2232043-7


PCB Mount Header, Vertical, Wire-to-Board, 7 Position, 5 mm [.197 in] Centerline, Fully Shrouded, Silver, Through Hole - Solder, RAST

5 IDC Connectors


View on TE.com >



### Connectors > PCB Connectors > PCB Headers & Receptacles











Connector System: Wire-to-Board

Number of Positions: 7
Number of Rows: 1

Centerline (Pitch): 5 mm [.197 in]
PCB Mount Orientation: Vertical

**Features** 

### **Product Type Features**

Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header
Configuration Features	
Keying & Polarized Position Locations	3D, 7D
Number of Positions	7
Number of Rows	1
PCB Mount Orientation	Vertical
Electrical Characteristics	
Operating Voltage	250 VAC

Natural

**Body Features** 

Primary Product Color



Contact Features	
Contact Mating Area Length	8.5 mm[.33 in]
PCB Contact Termination Area Plating Material Thickness	3.8 μm[149.606 μin]
Contact Layout	Inline
Mating Tab Width	6.3 mm[.248 in]
Mating Tab Thickness	.8 mm[.032 in]
Contact Mating Area Plating Material Thickness	1 μm[39.37 μin]
Contact Shape & Form	Square
Contact Mating Area Plating Material Finish	Matte
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Silver
Contact Type	Tab
Contact Current Rating (Max)	16 A
ermination Features	
Square Termination Post & Tail Dimension	.8 mm[.032 in]
Termination Post & Tail Length	3.5 mm[.138 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
PCB Mount Alignment Type	Polarizing Pegs
Mating Alignment Type	Keyed, Polarization
Mating Retention	With
Mating Retention Type	Latch
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	Without
lousing Features	
Housing Material	Nylon
Centerline (Pitch)	5 mm[.197 in]
Dimensions	
Connector Length	42.3 mm[1.67 in]



Connector Height	12.8 mm[.5 in][.503 in]
PCB Thickness (Recommended)	1.5 mm[.06 in]
Row-to-Row Spacing	5 mm[.197 in]
Usage Conditions	
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
UL Flammability Rating	UL 94V-0
UL Flammability Rating  Packaging Features	UL 94V-0
	UL 94V-0 45

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



## Compatible Parts



TE Part # 2232043-5 5P, RAST 5 Tab Header, THV



TE Part # 2232043-3 3P, RAST 5 Tab Header, THV



TE Part # 2232512-5 5P, RAST 5 Tab Header, THV



TE Part # 1971845-7 7P, RAST 5 Tab Header, THV



TE Part # 1971846-7 7P, RAST 5 Tab Header, THV



TE Part # 1971846-8 8P, RAST 5 Tab Header, THV



TE Part # 2232043-4 4P, RAST 5 Tab Header, THV



TE Part # 2232043-6 6P, RAST 5 Tab Header, THV



TE Part # 2232043-8 8P, RAST 5 Tab Header, THV



TE Part # 2232044-2 2P, RAST 5 Tab Header, THV



TE Part # 2232044-4 4P, RAST 5 Tab Header, THV



TE Part # 2232044-5 5P, RAST 5 Tab Header, THV



TE Part # 2232044-6 6P, RAST 5 Tab Header, THV



TE Part # 2232044-7 7P, RAST 5 Tab Header, THV



TE Part # 2232044-8 8P, RAST 5 Tab Header, THV



TE Part # 2232511-6 6P, RAST 5 Tab Header, THV



Also in the Series | RAST 5 IDC Connectors





Automotive Terminals(8)



Connector Contacts(12)



Crimp Terminal Housings(41)



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(417)



Rectangular Connector Housings(1)



Standard Edge Connectors(34)



Standard Rectangular Connectors(68)



Wire-to-Board Connector Assemblies & Housings(214)



Wire-to-Board Connector Contacts(2)


# Customers Also Bought




TE Part #5-103669-1
02 MTE HDR SRST LATCH W/HLDWN



TE Part #1744429-7
3.96 EP HDR ASSY 7P W/PEGS, GW



TE Part #1-2029265-2 12P VAL-U-LOK VRTHDR W/PGS GW



TE Part #2029265-2
2P VAL-U-LOK VRTHDR W/PGS GW



TE Part #6-1415899-4 RZHH-1A4-D005



TE Part #2232043-3 3P, RAST 5 Tab Header, THV



TE Part #1-1971922-1 6/11P,RAST 2.5 TabHeader,Ex-Locking,THV



TE Part #1744429-2 3.96 EP HDR ASSY 2P W/PEGS, GW

### **Documents**



### **Product Drawings**

7P, RAST 5 Tab Header, THV

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2232043-7\_A\_c-2232043-7-a.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2232043-7\_A\_c-2232043-7-a.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2232043-7\_A\_c-2232043-7-a.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### **Product Specifications**

**Product Specification** 

English

### **Product Environmental Compliance**

**Product Compliance** 

English

**Product Compliance** 

English

## Agency Approvals

**VDE** Certificate

English