

TE Internal #: 2274000-1

SFP, SFP+ & zSFP+, Cage Assembly, Data Rate (Max) 32 Gb/s, Internal/External EMI Springs, zSFP+ Thermally Enhanced, With

Lightpipe, 1 x 1, Dual Round

View on TE.com >



Connectors > Pluggable IO Connectors & Cages > SFP, SFP+ & zSFP+ > zSFP+ Cage Assembly: EMI Springs



Pluggable I/O Product Type: Cage Assembly

Data Rate (Max): 32 Gb/s

EMI Containment Feature Type: Internal/External EMI Springs

Pluggable I/O Applications: zSFP+ Thermally Enhanced

Lightpipe Options: With Lightpipe

All zSFP+ Cage Assembly: EMI Springs (25)

Features

Product Type Features

Form Factor	zSFP+
Cage Type	Single
Pluggable I/O Product Type	Cage Assembly
Lightpipe Options	With Lightpipe
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Port Matrix Configuration	1 x 1
Lightpipe Configuration	Dual Round
Lightpipe Style	Standard
Lightpipe Profile	Standard
Number of Ports	1

Electrical Characteristics

Data Rate (Max)	32 Gb/s
_ s. cs. 1 ta cs (1 ta cs. 4	0_ 0.5, 0

Termination Features



Termination Post & Tail Length	3 mm[.118 in]
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Cage Material	Nickel Silver Alloy
Dimensions	
PCB Thickness (Recommended)	1.5 mm[.059 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Heat Sink Compatible	No
For Use With Pluggable I/O Products	zSFP+ SMT Connector
Pluggable I/O Applications	zSFP+ Thermally Enhanced
Circuit Application	Signal
Packaging Features	
Packaging Method	Tray
Other	

Product Compliance

EMI Containment Feature Type

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Internal/External EMI Springs



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach




Customers Also Bought





TE Part #5120527-1 1FHP,64,30A/S,S,N,S10,12,13,15



TE Part #5120521-1 1FHR,64,30A/S,S,N,S08,09,10



68 50SR R/A RCPT ASSY,RDSN L/F



TE Part #1367073-1 20 POS SMT CONN, SFP, 15AU



TE Part #6469085-1 HMZD 3PAIR, HDR ASSY, 25MM MOD



TE Part #1761987-9 ReceptacleConnAssm38PosTape/Re



TE Part #1747253-1 UNC 4-40 SCREW KIT 1000 EACH A







Documents

Product Drawings

ZSFP+ 1X1 CAGE ASSEMBLY PRESSFIT WITH LP

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2274000-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2274000-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2274000-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

SFP, SFP+ & zSFP+, Cage Assembly, Data Rate (Max) 32 Gb/s, Internal/External EMI Springs, zSFP+ Thermally Enhanced, With Lightpipe, 1 x 1, Dual Round



zSFP+ Interconnect Brochure

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English