

TE Internal #: 2274680-1 Mini-SAS HD, Receptacle, Cable-to-Board, 144 Position, 4 Row, 4 Port, Right Angle, Through Hole - Press-Fit, .029 in [.75 mm] Centerline, Signal

View on TE.com >



Connectors > PCB Connectors > SAS & MiniSAS



SAS Connector Type: Mini-SAS HD Connector & Housing Type: Receptacle

Connector System: Cable-to-Board

Number of Positions: 144

Number of Rows: 4

Features

Product Type Features

Shell	With
SAS Connector Type	Mini-SAS HD
Connector & Housing Type	Receptacle
Connector System	Cable-to-Board

Connector & Contact Terminates To	Printed Circuit Board	
Configuration Features		
Number of Positions	144	
Number of Rows	4	
Number of Ports	4	
PCB Mount Orientation	Right Angle	
Body Features		
Primary Product Color	Black	
Contact Features		
Contact Base Material	Copper Alloy	
Termination Features		
Termination Method to Printed Circuit Board	Through Hole - Press-Fit	
Mechanical Attachment		
PCB Mount Retention	With	

2274680-1

Mini-SAS HD, Receptacle, Cable-to-Board, 144 Position, 4 Row, 4 Port, Right Angle, Through Hole - Press-Fit, .029 in [.75 mm] Centerline, Signal



PCB Mount Retention Type	M2 Screw
Connector Mounting Type	Board Mount, Panel Mount
Housing Features	
Housing Material	LCP (Liquid Crystal Polymer)
Centerline (Pitch)	.75 mm[.029 in]
Dimensions	
Profile Height from PCB	12.78 mm[.503 in]
Usage Conditions	
High Temperature Housing	Yes
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	15
Packaging Method	Box & Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant	
EU ELV Directive 2000/53/EC	Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC	
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free	
Solder Process Capability	Not applicable for solder process capability	
Product Compliance Disclaimer		

2274680-1

Mini-SAS HD, Receptacle, Cable-to-Board, 144 Position, 4 Row, 4 Port, Right Angle, Through Hole - Press-Fit, .029 in [.75 mm] Centerline, Signal



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought



S (tottlot = TE		The issue	
TE Part #1462052-3	TE Part #5-1393789-1	TE Part #2274215-1	TE Part #554808-1
HF6 53=50OHM140MW 5V MONO	V23079G2003B301	MINISAS HD 1X1 REC ASSY	HDW KIT, STDOFF STUD METRIC
TE Part #825440-5	TE Part #87220-3	TE Part #5-146281-3	TE Part #350211-1
MOD 2 PINHDR 2X05P.	03 MODII HDR SRST UNSHRD .100	03 MODII HDR SRST B/A LF	04P CMNL HDR ASSY PC

2274680-1

Mini-SAS HD, Receptacle, Cable-to-Board, 144 Position, 4 Row, 4 Port, Right Angle, Through Hole - Press-Fit, .029 in [.75 mm] Centerline, Signal





Documents

Product Drawings MINISAS HD 1X4 REC ASSY W/ WELD; AU ONLY

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2274680-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2274680-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2274680-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English