TE Internal #: 2274843-2

CFP, CFP2 & CFP4, Cage Assembly, 1 x 1, Data Rate (Max) 56 Gb/s,

Double-Sided (Belly-to-Belly) Mount, Cable-to-Board, Printed

Circuit Board, Signal

View on TE.com >



Connectors > Pluggable IO Connectors & Cages > CFP, CFP2 & CFP4











Pluggable I/O Product Type: Cage Assembly

Port Matrix Configuration: 1 x 1

Data Rate (Max): 56 Gb/s

PCB Mounting Style: Double-Sided (Belly-to-Belly)

Connector System: Cable-to-Board

Features

Product Type Features

Form Factor	CFP2
Cage Type	Single
Pluggable I/O Product Type	Cage Assembly
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Port Matrix Configuration	1 x 1
Electrical Characteristics	
Data Rate (Max)	56 Gb/s
Body Features	

Nickel

Aluminum Alloy

Contact Features

Primary Product Plating Material

Primary Product Material



Contact Current Rating (Max)	.5 A
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Mechanical Attachment	
PCB Mounting Style	Double-Sided (Belly-to-Belly)
Connector Mounting Type	Board Mount
Dimensions	
PCB Thickness (Recommended)	3 mm
Product Width	45.2 mm
Product Length	93.2 mm
Usage Conditions	
Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
Operation/Application	
Heat Sink Compatible	Yes
For Use With Pluggable I/O Products	CFP Assembly
Circuit Application	Signal
Packaging Features	
Packaging Method	Box & Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought











ASSY,120 POS PC104 PLUS LF













Documents

Product Drawings

CAGE ASSEMBLY, CFP2, 1X1

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2274843-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2274843-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2274843-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English