## SFP28 | XFP

TE Internal #: 2303074-1

XFP, Cage Assembly, Double-Sided (Belly-to-Belly) Mount, 1 Port, 1

x 1, Data Rate (Max) 10 Gb/s, Cable-to-Board, Printed Circuit

Board, XFP


View on TE.com >



Connectors > Pluggable IO Connectors & Cages > XFP > XFP Cage Assemblies and Kits











Pluggable I/O Product Type: Cage Assembly

PCB Mounting Style: Double-Sided (Belly-to-Belly)

Number of Ports: 1

Port Matrix Configuration: 1x1

Data Rate (Max): 10 Gb/s

All XFP Cage Assemblies and Kits (22)

## **Features**

## **Product Type Features**

Pluggable I/O Accessory Type	Heat Sink
Connector & Housing Type	Receptacle
Form Factor	XFP
Cage Type	Single
Pluggable I/O Product Type	Cage Assembly
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	

Number of Ports	1
Port Matrix Configuration	1 x 1

### **Electrical Characteristics**



Data Data (May)	10 Ch /a
Data Rate (Max)	10 Gb/s
Body Features	
Primary Product Material	Aluminum
Cage Plating Material	Tin
Contact Features	
Contact Mating Area Plating Material	Gold
Termination Features	
Termination Post & Tail Length	2.05 mm
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Mechanical Attachment	
PCB Mounting Style	Double-Sided (Belly-to-Belly)
Connector Mounting Type	Board Mount
Housing Features	
Cage Material	Nickel Silver Alloy
Housing Material	LCP (Liquid Crystal Polymer)
Housing Color	Black
Dimensions	
Connector Profile Height	13.29 mm
Product Width	22 mm
Product Length	64.03 mm
Usage Conditions	
Operating Temperature Range	-10 – 70 °C
Operation/Application	
Heat Sink Application	Yes
Heat Sink Compatible	Yes
For Use With Pluggable I/O Products	XFP Connector
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Box & Tray
Other	



Pluggable I/O Connectors Comment	No elastomeric gasket.
Included Lightpipe	No

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


# **Compatible Parts**



Also in the Series | XFP









# Customers Also Bought













# **Documents**

## **Product Drawings**

XFP CAGE ASSEMBLY, W/O INTERMEDIATE GSKT

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2303074-1\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2303074-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2303074-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

XFP, Cage Assembly, Double-Sided (Belly-to-Belly) Mount, 1 Port, 1 x 1, Data Rate (Max) 10 Gb/s, Cable-to-Board, Printed Circuit Board, XFP



Product Specifications
Application Specification

English