TE Internal #: 2359615-4

ANSI Street Lighting Receptacles, Accessory, -40 – 85 °C [-40 – 185 °

F1

View on TE.com >



Connectors > Lighting Connectors > Street Lighting Controls > ANSI Street Lighting Receptacles











Lighting Product Type: Accessory

Operating Temperature Range: -40 - 85 °C [-40 - 185 °F]

Features

Product Type Features

Lighting Product Type	Accessory
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Industry Standards	
Agency/Standard	ANSI

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU ELV Directive 2000/53/EC China RoHS 2 Directive MIIT Order No 32, 2016 EU REACH Regulation (EC) No. 1907/2006 Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Perfluorobutane sulfonic acid (PFBS) and its salts (.13% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable	EU RoHS Directive 2011/65/EU	Compliant
EU REACH Regulation (EC) No. 1907/2006 Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Perfluorobutane sulfonic acid (PFBS) and its salts (.13% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable	EU ELV Directive 2000/53/EC	Compliant
(235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Perfluorobutane sulfonic acid (PFBS) and its salts (.13% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable	China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
governmental regulations relevant to your geographic location.	EU REACH Regulation (EC) No. 1907/2006	(235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Perfluorobutane sulfonic acid (PFBS) and its salts (.13% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after



Halogen Content

Low Bromine/Chlorine - Br and Cl < 900

ppm per homogenous material. Also BFR

/CFR/PVC Free

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2359482-1

LUMAWISE ENDURANCE N+ 7P Base
With Vent



TE Part # 2359482-2 LUMAWISE ENDURANCE N+ 7P Base



TE Part # 2359482-3 LUMAWISE ENDURANCE N+ 5P Base With Vent









Customers Also Bought

















Documents

Product Drawings

LUMAWISE ENDURANCE N+ Lt Gray Tall Dome

English

CAD Files

Customer View Model

ENG_CVM_CVM_2359615-4_A1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2359615-4_A1.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_2359615-4_A1.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

LUMAWISE ENDURANCE N+ Network Lighting Controls

English

Product Specifications

Application Specification

English

Agency Approvals

UL_CERT_CB_4789600659_TR_C1

English

UL_CERT_CB_US_37285_C1

English