

TE Internal #: 2406857-1

SMP RF Interface, Jack, 50  $\Omega$ , Push-On, 0 – 18 GHz Operating

Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, -40 –

125 °C [-40 – 257 °F]

View on TE.com >




#### Connectors > RF Connectors > Coax Connectors











RF Interface: SMP

RF Connector Style: Jack

Impedance:  $50 \Omega$ 

RF Connector Coupling Mechanism: Push-On

Operating Frequency: 0 – 18 GHz

### **Features**

### Product Type Features

RF Interface	SMP
RF Connector Style	Jack
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

### **Configuration Features**

PCB Mount Orientation	Vertical
Number of Positions	1
Number of Coaxial Contacts	1

### **Electrical Characteristics**

Impedance	50 Ω	
'		

### **Body Features**

Body Underplating Material	Nickel
Cable Connector Orientation	Straight



Body Material	Brass
Body Material Finish	Plated
Body Plating Material	Gold
Contact Features	
RF Connector Center Contact Plating Material	Gold
RF Connector Center Contact Material	Beryllium Copper
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
RF Connector Coupling Mechanism	Push-On
RF Contact Captivation Method	Mechanical
Detent	With
Usage Conditions	
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]
Operation/Application	
Operating Frequency	0 – 18 GHz
Circuit Application	Signal
Packaging Features	
Packaging Method	Bag
Other	
Dielectric Material	PTFE

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (4% in Component Part) Article Safe Usage Statements:



Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content	Low Bromine/Chlorine - Br and Cl < 900
	ppm per homogenous material. Also BFR /CFR/PVC Free

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts











# Customers Also Bought





TE Part #1658610-4 09 POS HDF RCPT, MS, LEAD FREE



TE Part #322797 SOLIS R HR 22-16COM 22-18MIL 6



TE Part #34107 SOLIS R 22-16 COMM 22-18 MIL 6





TE Part #34107-1
TERMINAL, SOLIS R 22-16 6



TE Part #3-2176091-8
RP 2A 0.25W 140R 0.1% 25PPM 1K RL



TE Part #6-2176305-0 RP 1E 0.1W 442R 0.1% 25PPM 5K RL





TE Part #8-1437627-4
G12KA=BUTTON GUARD KNURL
ALUM



### **Documents**

### **Product Drawings**

**SMP JACK ST PCB MOUNT** 

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2406857-1\_1.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2406857-1\_1.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2406857-1\_1.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

SMP RF Interface, Jack, 50  $\Omega$ , Push-On, 0 – 18 GHz Operating Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, -40 – 125 °C [-40 – 257 °F]



### 1307191 RF Coax Products Catalog

English

**Product Specifications** 

**Product Specification** 

English