

# AMP Superseal 1.5mm Series

TE Internal #: 281934-3


Single Wire Seal (SWS), Silicone, Red, 5.5 mm [.217 in] Cavity Diameter, .098 – .13 in [2.5 – 3.3 mm] Insulation Diameter, AMP

Superseal 1.5mm Series

View on TE.com >



Connectors > Connector Accessories > Connector Seals & Cavity Plugs



Connector Seal & Plug Type: Single Wire Seal (SWS)

Primary Product Material: Silicone

Primary Product Color: Red

Cavity Diameter: 5.5 mm [.217 in]

Compatible Insulation Diameter Range: 2.5 – 3.3 mm [ .098 – .13 in ]

# **Features**

# **Product Type Features**

Connector Seal & Plug Type	Single Wire Seal (SWS)
Body Features	
Primary Product Material	Silicone
Primary Product Color	Red
Dimensions	

#### Dimensions

Cavity Diameter	5.5 mm[.217 in]
Compatible Insulation Diameter Range	2.5 – 3.3 mm[.098 – .13 in]

# **Usage Conditions**

Operating Temperature (Max)	65 °C, 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C, 130 °C [149 °F][158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F][266 °F]
Operating Temperature Range	-40 - 130 °C[-40 - 266 °F]

# **Industry Standards**

UL Flammability Rating	None
------------------------	------

#### Other

Shore A Hardness 50	carbons
Shore A hardness	50



Contains Lubricant	Yes	

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





Also in the Series | AMP Superseal 1.5mm Series





Automotive Connector Caps & Covers (2)



Automotive Housings(29)




Automotive Terminals(17)





Insertion & Extraction Tools(3)



# Customers Also Bought









# **Documents**

Product Drawings
SINGLE WIRE SEAL

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_281934-3\_H.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_281934-3\_H.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_281934-3\_H.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.



# Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

**Product Specifications** 

AMP Superseal 1.5 series

English

English